

INDUSTRIAL COMPONENT DATA

E57SAL12A4E 136095 Y7-136095 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 4mm, 2L, 20-250VAC, M12, m..

Brand: EATON - MOELLER | Manufacturer Part Number: E57SAL12A4E



Manufacturer	EATON - MOELLER
MPN / Reference	E57SAL12A4E
Catalog number	Y7-136095
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-C714426479
Generated	2026-08-03

Product Overview

Proximity switch, inductive, 1N/O, Sn=4mm, 2L, 20-250VAC, M12, metal, line 2m

E57SAL12A4E

Proximity switch, E57 Premium+ Short-Series, 1 N/O, 2-wire, 40 - 250 V AC, M12 x 1 mm, Sn= 4 mm, Non-flush, Stainless steel, 2 m connection cable

Proximity switch, Inductive Sensors, Product range: E57 Premium+ Short-Series, Connection: 2-wire, Design (outer dimensions): M12 x 1 mm, Rated operational voltage: Ue= 40 - 250 V AC, Rated switching distance: Sn= 4 mm, Type of mounting: Non-flush, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Sensors

Additional Product Information

General specifications

Product Name Eaton Moeller® series E57 Proximity switch Catalog Number 136095 Model Code E57SAL12A4E EAN 4015081328888 Product Length/Depth 127 mm Product Height 154.94 mm Product Width 53.34 mm Product Weight 0.23 kg Certifications IEC/EN 60947-5-2

UL 508

CSA-C22.2 No. 14

UL File No.: E166051

UL

CSA File No.: 50513

CSA

CSA Class No.: 3211-03

CE

UL Category Control No.: NRKH, NRKH7 Product specifications

Type Inductive sensor Electric connection type Cable Enclosure material finishing Other Actuation type Metallic Target
Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust
None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None
Ambient operating temperature - max 70 °C Ambient operating temperature - min -25 °C Diameter sensor 12 mm Number
of contact energized outputs with signalling function 0 Number of contacts (normally open contacts) 1 Number of outputs
(protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with
signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 10 A Output current at protected output - max
0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 250 V Voltage type AC Mounting method Non-flush mounting
Material Stainless steel Connection type 2 m connection cable
2-wire Installation type Not flat Degree of protection IP67
NEMA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E57SAL12A4E with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.