

## INDUSTRIAL COMPONENT DATA

# SPCT2-075/3 167580 EATON ELECTRIC Plug-in surge arresters, 3p, 75VAC, 3x20kA

Brand: EATON - MOELLER | Manufacturer Part Number: SPCT2-075/3



|                 |                                                  |
|-----------------|--------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                  |
| MPN / Reference | SPCT2-075/3                                      |
| Catalog number  | 167580                                           |
| Category        | Surge protection device for power supply systems |
| Minimum order   | 1 Pcs                                            |
| Document ID     | EO-461E1542DF                                    |
| Generated       | 2026-08-04                                       |

## Product Overview

Plug-in surge arresters, 3p, 75VAC, 3x20kA

SPCT2-075/3

For protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgear

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

## Additional Product Information

Plug-in surge arresters, 3p, 75VAC, 3x20kAFor protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgearDelivery program

ProductsSurge arrestersApplication fieldResidential buildings

Utility buildings

Open areasTechnical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems

(EC000941)Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems ([email protected])

[ACN278011])System configuration DCNoSystem configuration ITNoSystem configuration TNYesSystem configuration

TN-CNoSystem configuration TN-C-SNoSystem configuration TN-SNoSystem configuration TTNoSystem configuration  
otherYesNumber of conductors (without earthing)3Nominal discharge surge current (8/20)15 kANominal voltage AC75  
VNominal voltage DC0 VShort-circuit breaking capacity (I<sub>sc</sub>)0 kAMax. continuous voltage AC75 VMax. discharge surge  
current (8/20)30 kAMax. continuous voltage DC0 VMounting methodDIN rail (top hat rail) 35 mmConstruction size3 modular  
spacingMax. PV-voltage0 VVoltage protection level0.55 kVMax. conductor cross section solid (solid...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPCT2-075/3 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.