

INDUSTRIAL COMPONENT DATA

SPCT2-135 167582 EATON ELECTRIC Surge arrester plug-in unit, 135VAC, 20 kA

Brand: EATON - MOELLER | Manufacturer Part Number: SPCT2-135



Manufacturer	EATON - MOELLER
MPN / Reference	SPCT2-135
Catalog number	167582
Category	Surge protection device for power supply systems
Minimum order	2 Pcs
Document ID	EO-5F37291BB2
Generated	2026-08-01

Product Overview

Surge arrester plug-in unit, 135VAC, 20 kA

SPCT2-135

For protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgear

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

Surge arrester plug-in unit, 135VAC, 20 kAFor protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgearDelivery program

ProductsSurge arrestersApplication fieldResidential buildings

Utility buildings

Open areasTechnical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems

(EC000941)Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems ()

[ACN278011])System configuration DCNoSystem configuration ITNoSystem configuration TNYesSystem configuration

TN-CNoSystem configuration TN-C-SNoSystem configuration TN-SNoSystem configuration TTNoSystem configuration
otherYesNumber of conductors (without earthing)0Nominal discharge surge current (8/20)20 kANominal voltage AC135
VNominal voltage DC0 VShort-circuit breaking capacity (I_{sc})0 kAMax. continuous voltage AC135 VMax. discharge surge
current (8/20)40 kAMax. continuous voltage DC0 VMounting methodOn basic elementConstruction size1 modular
spacingMax. PV-voltage0 VVoltage protection level0.8 kVMax. conductor cross section solid (solid, stranded)0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPCT2-135 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.