

INDUSTRIAL COMPONENT DATA

SPCT2-335 167597 Y7-167597 EATON ELECTRIC Surge arrester plug-in unit, 335VAC, 20 kA

Brand: EATON - MOELLER | Manufacturer Part Number: SPCT2-335



Manufacturer	EATON - MOELLER
MPN / Reference	SPCT2-335
Catalog number	Y7-167597
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-90E217F119
Generated	2026-08-03

Product Overview

Surge arrester plug-in unit, 335VAC, 20 kA

SPCT2-335

Eaton Moeller series xPole - SPCT2 Surge Protection Device. Surge arrester plug-in unit, 335VAC, 20 kA

For protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgear

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - SPCT2 Surge protection device Catalog Number 167597 Model Code SPCT2-335 EAN 4015081640881 Product Length/Depth 47 mm Product Height 54 mm Product Width 17.5 mm Product Weight 0.047 kg Compliances RoHS conform Delivery program

Application Type Surge arrester Technical data - electrical

Voltage protection level 1.6 KV Voltage protection level (L-N) 0 KV Voltage protection level (N-PE) 0 KV Nominal voltage at AC 335 V Nominal voltage at DC 0 V Continuous voltage at AC - max 335 V Continuous voltage at DC - max 0 V PV-voltage - max 0 V Nominal discharge surge current (8/20) 20 kA Discharge surge current (8/20) - max 40 kA

Short-circuit breaking capacity (ISCCR) 0 kA Signalling at the device Optic Technical data - mechanical

Frame 1 modular spacing Mounting method On basic element Number of conductors without earthing 0 Conductor cross

section (flexible, fine-strand) - min 0 mm² Conductor cross section (flexible, fine-strand) - max 0 mm² Conductor cross section (solid, solid-strand) - min 0 mm² Conductor cross section (solid, solid-strand) - max 0 mm² Degree of protection IP20

Additional information

Features Category type 2 System configuration type TN

Other

ETIM for 167597 Earthing, lightning and surge protection (EC000941)

Feature Name

Feature Value

System configuration DC (EF009926)

No

System configuration IT (EF009927)

No

System configuration TN (EF009928)

Yes

System configuration TN-C (EF009929)

No

System conf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPCT2-335 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.