

INDUSTRIAL COMPONENT DATA

SPCT2-NPE60/1 167618 Y7-167618 EATON ELECTRIC Plug-in surge arresters, 1pole, 260VAC, 30 kA

Brand: EATON - MOELLER | Manufacturer Part Number: SPCT2-NPE60/1



Manufacturer	EATON - MOELLER
MPN / Reference	SPCT2-NPE60/1
Catalog number	Y7-167618
Category	Surge protection device for power supply systems
Minimum order	1 Pcs
Document ID	EO-4B65A38E7D
Generated	2026-08-02

Product Overview

Plug-in surge arresters, 1pole, 260VAC, 30 kA

SPCT2-NPE60/1

Eaton Moeller series xPole - SPCT2 Surge Protection Device. Plug-in surge arresters, 1pole, 260VAC, 30 kA

For protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgear caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, SPC-S-HK auxiliary contact for remote signaling can be added, can be bussed with all Xtra Combinations switchgear

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Industrial

Additional Product Information

General specifications

Product Name Eaton Moeller series xPole - SPCT2 Surge protection device Catalog Number 167618 Model Code SPCT2-NPE60/1 EAN 4015081641086 Product Length/Depth 80 mm Product Height 67 mm Product Width 17.5 mm Product Weight 0.084 kg Compliances RoHS conform Product specifications

Type Surge arrester Application Open areasResidential buildingsUtility buildings Features Category type 2 Frame 1 modular spacing Degree of protection IP20 Mounting method DIN rail (top hat rail) 35 mm Voltage protection level (L-N) 0 KV Voltage protection level (N-PE) 0 KV Signalling at the device Optic System configuration type TN Other Conductor cross section (flexible, fine-strand) - max 35 mm² Conductor cross section (flexible, fine-strand) - min 35

mm² Conductor cross section (solid, solid-strand) - max 25 mm² Conductor cross section (solid, solid-strand) - min 25 mm²
Continuous voltage at AC - max 260 V Continuous voltage at DC - max 0 V Discharge surge current (8/20) - max 60 kA
Nominal discharge surge current (8/20) 30 kA Nominal voltage at AC 260 V Nominal voltage at DC 0 V Number of
conductors without earthing 0 PV-voltage - max 0 V Short-circuit breaking capacity (ISCCR) 0 kA Voltage protection level 1
KV Overcurrent protection device, parallel connection (fuse) - max 0 A Overcurrent protection device, series connection
(fuse) - max 125 A Integrated short-circuit protection selective to fuse gG 0 A
ETIM for 167618 Earthing, lightning and surge protection (EC000941)
F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPCT2-NPE60/1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.