


**INDUSTRIAL COMPONENT DATA**

# 134LQ25 091449 EATON ELECTRIC Insert label, transparent, LINKS

Brand: EATON - MOELLER | Manufacturer Part Number: 134LQ25



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | 134LQ25                               |
| Catalog number  | 091449                                |
| Category        | Hood/lens for circuit control devices |
| Minimum order   | 20 Pcs                                |
| Document ID     | EO-9AE19596B6                         |
| Generated       | 2026-08-05                            |

## Product Overview

Insert label, transparent, LINKS

Indicator plate. Transparent. Registration: LINKS. For RMQ16 25x25

Practical transparent insert plate with printed symbols, ready for use on RMQ16 illuminated pushbuttons and flat indicator lights with front dimensions 25x25 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

Insert label, transparent, LINKS Practical transparent insert plate with printed symbols, ready for use on RMQ16 illuminated pushbuttons and flat indicator lights with front dimensions 25x25 mm Delivery program

Product range Accessories Basic function accessories Transparent insert plates Single unit/Complete unit Single unit

Inscription LINKS Colour Front dimensions 25 x 25 Connection to SmartWire-DT no Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C

Operating ambient temperature max. +60 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2

Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2

Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of

materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects Meets the product standard's requirements. 10.2 Strength of materials...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 134LQ25 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.