

## INDUSTRIAL COMPONENT DATA

# 40LQ18 086178 EATON ELECTRIC Insert label, transparent, manual operation

Brand: EATON - MOELLER | Manufacturer Part Number: 40LQ18



|                 |                                       |
|-----------------|---------------------------------------|
| Manufacturer    | EATON - MOELLER                       |
| MPN / Reference | 40LQ18                                |
| Catalog number  | 086178                                |
| Category        | Hood/lens for circuit control devices |
| Minimum order   | 20 Pcs                                |
| Document ID     | EO-CD09FE4BA2                         |
| Generated       | 2026-08-04                            |

## Product Overview

Insert label, transparent, manual operation

Indicator plate. Transparent. Registration: manual operation. For RMQ16 18x18

Practical transparent insert plate with printed symbols, ready for use on RMQ16 illuminated pushbuttons and flat indicator lights with front dimensions 18x18 mm

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                             |
|--------------|-------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Auxiliary Control and Signalling Elements |
|--------------|-------------------------------------------------------------|

## Additional Product Information

Insert label, transparent, manual operation Practical transparent insert plate with printed symbols, ready for use on RMQ16 illuminated pushbuttons and flat indicator lights with front dimensions 18x18 mm Delivery program

Product range Accessories Basic function accessories Transparent insert plates Single unit/Complete unit Single unit Name

Hand Colour Front dimensions 18 x 18 Connection to SmartWire-DT no Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C

Operating ambient temperature max. +60 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2

Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2

Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric

effects Meets the product standard's requirements. 10.2 Strength of materi...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 40LQ18 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.