

INDUSTRIAL COMPONENT DATA

Z-SCH230/1/25-20 120853 Y7-120853 EATON ELECTRIC

Installation contactor, 230VAC, 2N/O, 25A

Brand: EATON - MOELLER | Manufacturer Part Number: Z-SCH230/1/25-20



Manufacturer	EATON - MOELLER
MPN / Reference	Z-SCH230/1/25-20
Catalog number	Y7-120853
Category	Installation contactor for distribution board
Minimum order	1 Pcs
Document ID	EO-2D3E14992C
Generated	2026-08-05

Product Overview

Installation contactor, 230VAC, 2N/O, 25A

Z-SCH230/1/25-20

Eaton Distribution parts. Installation contactor, 230VAC, 2N/O, 25A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

General specifications

Product Name Eaton Distribution parts Catalog Number 120853 Model Code Z-SCH230/1/25-20 EAN 4015081186839

Product Length/Depth 65 mm Product Height 85 mm Product Width 17.7 mm Product Weight 0.14 kg Compliances RoHS conform Product specifications

Amperage Rating 25 A Features Additional equipment possible Degree of protection IP40 Equipment heat dissipation, current-dependent 7.2 W Ambient operating temperature - max 60 °C Ambient operating temperature - min -40 °C Heat dissipation capacity 0 W Heat dissipation per pole, current-dependent 0 W Incandescent lamp load - max 3000 W Load fluorescent lamp - max 1160 VA Load fluorescent lamp (duo circuit) - max 2552 VA Load fluorescent lamp (parallel compensated) - max 1044 VA Number of contacts (normally closed contacts) 0 Number of contacts (normally open contacts) 2 Number of modular spacings 1 Rated operating voltage (Ue) - max 440 V Rated operating voltage (Ue) - min 440 V Rated operational current for specified heat dissipation (In) 25 A Static heat dissipation, non-current-dependent 0 W Utility category 1 Voltage rating (excitation) - max 253 V Voltage rating (excitation) - min 195.5 V Built-in depth 60 mm Voltage type AC Utilization category (according to EN IEC 60947-4-1) AC-1

ETIM for 120853 Modular devices for distribution board/surface mounting (EC001653)

Feature Name

Feature Value

Rated operating voltage (EF001435)

440 V

Rated operation current (EF007679)

25 A

Utilization category according to EN...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-SCH230/1/25-20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.