

INDUSTRIAL COMPONENT DATA

Z-R230/S 265149 EATON ELECTRIC Installation relay, 230VAC/50Hz, 1N/O, 20A, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-R230/S



Manufacturer	EATON - MOELLER
MPN / Reference	Z-R230/S
Catalog number	265149
Category	Installation relay
Minimum order	1 Pcs
Document ID	EO-77F6C50F51
Generated	2026-08-06

Product Overview

Installation relay, 230VAC/50Hz, 1N/O, 20A, 1HP

Installation relay with manual operation, control voltage 230V 50Hz, function: 1 N/O, rated operational current 20 A, 250V AC, type conform to IEC/EN 60947, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-10 mm² solid and flexible / 0.5-6 mm² flexible with ferrule

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

Installation relay, 230VAC/50Hz, 1N/O, 20A, 1HP Installation relay with manual operation, control voltage 230V 50Hz, function: 1 N/O, rated operational current 20 A, 250V AC, type conform to IEC/EN 60947, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-10 mm² solid and flexible / 0.5-6 mm² flexible with ferrule [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 20 A Heat dissipation per pole, current-dependent [Pvid] 2 W Equipment heat dissipation, current-dependent [Pvid] 4.4 W Operating ambient temperature min. -20 °C Operating ambient temperature max. +45 °C , Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652) Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board () [AFZ821014]) Function Mechanical Mounting method DIN rail Width in number of modular spacings 1 Built-in depth 60 mm Number of contacts as normally open contact 1 Number of contacts as normally closed contact 0 Number of contacts as change-over contact 0 Control voltage 1 230 - 230

V Type of control voltage 1 AC Frequency control voltage 1 50 - 50 Hz Control voltage 2 0 - 0 V Type of control voltage 2
AC/DC Frequency control voltage 2 0 - 0 Hz Rated current 20 A S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-R230/S with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.