

INDUSTRIAL COMPONENT DATA

Z-R240/SS 285525 EATON ELECTRIC Installation relay, 240V 50Hz, 2N/O

Brand: EATON - MOELLER | Manufacturer Part Number: Z-R240/SS



Manufacturer	EATON - MOELLER
MPN / Reference	Z-R240/SS
Catalog number	285525
Category	Installation relay
Minimum order	1 Pcs
Document ID	EO-A9A6EE3DE8
Generated	2026-08-06

Product Overview

Installation relay, 240V 50Hz, 2N/O

High-quality residual current circuit-breaker/miniature circuit-breaker with overcurrent protection independent of mains voltage, contact position display red-green, terminal rear plug protection, tri-stable slide catch-enables removal from an existing closure assembly, comprehensive accessory product range can be retrofitted, wide range of rated fault currents, rated operational currents up to 40 A, trip types B, Cc, D, rated switching capacity 10 kA, suitable for use in the free (on-site power and outdoor distribution board) to -25 °C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Modular Switchgear - Others and Accessories

Additional Product Information

Installation relay, 240V 50Hz, 2N/O High-quality residual current circuit-breaker/miniature circuit-breaker with overcurrent protection independent of mains voltage, contact position display red-green, terminal rear plug protection, tri-stable slide catch-enables removal from an existing closure assembly, comprehensive accessory product range can be retrofitted, wide range of rated fault currents, rated operational currents up to 40 A, trip types B, Cc, D, rated switching capacity 10 kA, suitable for use in the free (on-site power and outdoor distribution board) to -25 °C [Design verification as per IEC/EN 61439

Rated operational current for specified heat dissipation [In] 20 A Heat dissipation per pole, current-dependent [Pvid] 2 W Equipment heat dissipation, current-dependent [Pvid] 6.4 W Operating ambient temperature min. -20 °C Operating ambient temperature max. +45 °C , Technical data ETIM 7.0

Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652) Electric engineering,

automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board ( [AFZ821014]) Function Mechanical Mounting method DIN rail Width in number of modular spacings 1 Built-in depth 60 mm Number of contacts as normally open contact 2 Number of contacts as normally closed contact 0 Number of contacts as change-over contact 0 Control vol...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-R240/SS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.