

INDUSTRIAL COMPONENT DATA

Z-R24/SS 265173 4133965 EATON ELECTRIC Installation relay, 24VAC/50Hz, 2N/O, 20A, 1HP

Brand: EATON - MOELLER | Manufacturer Part Number: Z-R24/SS



Manufacturer	EATON - MOELLER
MPN / Reference	Z-R24/SS
Catalog number	4133965
Category	Installation relay
Minimum order	1 Pcs
Document ID	EO-01AF0DEE88
Generated	2026-08-06

Product Overview

Installation relay, 24VAC/50Hz, 2N/O, 20A, 1HP

Installation relay with manual operation, control voltage 24V 50Hz, function: 2 N/O, rated operational current 20 A, 250V AC, type conform to IEC/EN 60947, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-10 mm² solid and flexible / 0.5-6 mm² flexible with ferrule

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Others and Accessories
--------------	---

Additional Product Information

EL-Nummer (Norway)4133965Installation relay, 24VAC/50Hz, 2N/O, 20A, 1HPInstallation relay with manual operation, control voltage 24V 50Hz, function: 2 N/O, rated operational current 20 A, 250V AC, type conform to IEC/EN 60947, standard front dimension 45 mm, mounting width 1 SU (17.5mm), top-hat rail mounting, terminal cross-section 0.5-10 mm² solid and flexible / 0.5-6 mm² flexible with ferruleDesign verification as per IEC/EN 61439
Rated operational current for specified heat dissipation [In]20 AHeat dissipation per pole, current-dependent [Pvid]2
WEquipment heat dissipation, current-dependent [Pvid]6.4 WOperating ambient temperature min.-20 °COperating ambient temperature max.+45 °CTechnical data ETIM 7.0
Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652)Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board ( [AFZ821014])FunctionMechanicalMounting methodDIN railWidth in number of modular spacings1Built-in depth60 mmNumber of contacts as normally open contact2Number of contacts as normally closed contact0Number of contacts as change-over contact0Control voltage 124 -

24 VType of control voltage 1ACFrequency control voltage 150 - 50 HzControl voltage 20 - 0 VType of control voltage 2AC/DCFrequency control voltage 20 - 0 HzRated current20 ASupply voltage250 - 250 VV...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / Z-R24/SS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.