

INDUSTRIAL COMPONENT DATA

T0-1-91/E 072082 Y7-72082 EATON ELECTRIC step switch for heating, Contacts: 2, 20 A, front plate: 0-2, 60 °,..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-1-91/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-1-91/E
Catalog number	Y7-72082
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-D59C64DCCC
Generated	2026-08-05

Product Overview

step switch for heating, Contacts: 2, 20 A, front plate: 0-2, 60 °, 2 steps, 60°, maintained, flush mounting

Step switch for heating 2 poles 20 A Plate

Eaton Moeller® series T0 step switch for heating, T0, 20 A, flush mounting, 1 contact unit(s), Contacts: 2, 60 °, maintained, With 0 (Off) position, 0-2, Design number 91

Step switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 2, Number of steps: 2 steps, 60°, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 1 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 072082 Model Code T0-1-91/E EAN 4015080720829

Product Length/Depth 76 mm Product Height 48 mm Product Width 48 mm Product Weight 0.083 kg Certifications

CSA-C22.2 No. 94

UL File No.: E36332

CE

IEC/EN 60947

CSA Class No.: 3211-05

IEC/EN 60947-3

CSA File No.: 012528

UL Category Control No.: NLRV

UL

UL 60947-4-1

CSA

VDE 0660

IEC/EN 60204

CSA-C22.2 No. 60947-4-1-14 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 072082 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

1

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF001596)

Pl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-1-91/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.