

INDUSTRIAL COMPONENT DATA

T0-3-38/EZ 013334 Y7-13334 EATON ELECTRIC Multi-speed switches, Contacts: 5, 20 A, 2 speeds, 2 separate wind..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-38/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-3-38/EZ
Catalog number	Y7-13334
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-1A977EC727
Generated	2026-08-05

Product Overview

Multi-speed switches, Contacts: 5, 20 A, 2 speeds, 2 separate windings, front plate: 2-0-1, 60 °, maintained, centre mounting, SOND 29

Multi-speed switch. 5 poles. 20 A. 2 speeds. 2 windings

Multi-speed switches, T0, 20 A, centre mounting, 3 contact unit(s), Contacts: 5, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 29, Design number 38

Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 29, Contacts: 5, Degree of Protection: Front IP65, Design: center mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Multi-speed switches, T0, 20 A, centre mounting, 3 contact unit(s), Contacts: 5, 60 °, maintained, With 0 (Off) position, 2-0-1, SOND 29, Design number 38Multi-speed switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 29, Contacts: 5, Degree of Protection: Front IP65, Design: center mounting, switching function: 2 speeds, 2 separate windings, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 2-0-1, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 3 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN

60947-3

General specifications Product name Eaton Moeller® series T0 Multi-speed switch Part no. T0-3-38/EZEAN4015080133346 Product Length/Depth 115 millimetre Product height 48 millimetre Product width 48 millimetre Product weight 0.153 kilogram Certifications CSA-C22.2 No. 94

UL

VDE 0660

IEC/EN 60204

IEC/EN 60947-3

IEC/EN 60947

CSA File No.: 012528

UL Category Control No.: NLRV

UL File No.: E36332

UL 60947-4-1

CSA

CE

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

UL

CSA Product Tradename T0 Product Type Multi-speed switch Product Sub Type None Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second Features & Functions Enclosure material Plastic Fitted with: Black thumb grip and front plate

0 (off) position Inscription 2-0-1 Number of poles 3 Switch function type 2 speeds, 2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-38/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.