

INDUSTRIAL COMPONENT DATA

T0-4-15602/EZ 031741 Y7-31741 EATON ELECTRIC Coding switches, Contacts: 8, 20 A, Binary BCD code 0-9, front ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-4-15602/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T0-4-15602/EZ
Catalog number	Y7-31741
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-135CE5457D
Generated	2026-08-06

Product Overview

Coding switches, Contacts: 8, 20 A, Binary BCD code 0-9, front plate: 0-9, 30 °, maintained, centre mounting

Encoder switch 8 poles 20 A BCD Code 0-9 Indicator Plate:

Eaton Moeller® series T0 Coding switches, T0, 20 A, centre mounting, 4 contact unit(s), Contacts: 8, 30 °, maintained, With 0 (Off) position, 0-9, Design number 15602

Coding switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 8, Degree of Protection: Front IP65, Design: center mounting, switching function: Binary BCD code 0-9, Switching angle: 30 °, Switching performance: maintained, With 0 (Off) position, 4 contact unit(s), Rated uninterrupted current: I_u = 20 A, front plate: 0-9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Coding switch Catalog Number 031741 Model Code T0-4-15602/EZ EAN 4015080317418 Product Length/Depth 125 mm Product Height 48 mm Product Width 48 mm Product Weight 0.177 kg

Certifications IEC/EN 60947

CSA Class No.: 3211-05

UL Category Control No.: NLRV

VDE 0660

CE

IEC/EN 60947-3

UL File No.: E36332

CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

CSA

IEC/EN 60204

UL 60947-4-1

UL

CSA File No.: 012528 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 031741 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Coding switch

Number of poles (EF001391)

0

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

10

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-4-15602/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.