

INDUSTRIAL COMPONENT DATA

E-PKZ0-G 072907 Y7-72907 EATON ELECTRIC Insulated enclosure, flush mounting, rotary handle black grey, IP55 x

Brand: EATON - MOELLER | Manufacturer Part Number: E-PKZ0-G



Manufacturer	EATON - MOELLER
MPN / Reference	E-PKZ0-G
Catalog number	Y7-72907
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-839D768DCC
Generated	2026-08-04

Product Overview

Insulated enclosure, flush mounting, rotary handle black grey, IP55_x

IP55 Recessed Insulating Box For PKZ01 + Rotary Knob

Eaton Moeller® series E-PKZ0 Insulated enclosure, E-PKZ0, H x W x D = 129 x 85 x 124 mm, flush-mounted, rotary handle, black/gray, IP55

Insulated enclosure for flush mounting, for PKZM0, degree of protection IP55 integrated terminal for PE(N) connection., Per 2 M25 knockout cable entries, with black-grey rotary knob

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series E-PKZ0 Accessory Insulated enclosure Catalog Number 072907 Model Code E-PKZ0-G EAN 4015080729075 Product Length/Depth 124 mm Product Height 129 mm Product Width 85 mm Product Weight 0.224 kg Certifications IEC/EN 60947-4-1

CSA Class No.: 3211-05

CSA-C22.2 No. 14

CE

CSA File No.: 165628

UL

UL 508

UL Category Control No.: NLRV

UL File No.: E36332

CSA Features & Functions

Enclosure material Plastic Fitted with: Black-gray rotary knob

PE(N) terminal General

Degree of protection (front side) NEMA 1

NEMA 12

IP55

NEMA 3R Model Built-in Product category Accessories Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation

Please enq...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E-PKZ0-G with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.