

INDUSTRIAL COMPONENT DATA

CI-K2-T3-2 207437 Y7-207437 EATON ELECTRIC Insulated enclosure, HxWxD 160x100x100mm, for T3-2

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K2-T3-2



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K2-T3-2
Catalog number	Y7-207437
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-2540B929EF
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=160x100x100mm, for T3-2

CI-K2-T3-2

Small enclosure, degree of protection IP65, glass-fiber reinforced polycarbonate, enclosure base RAL 9005, black/operator only RAL 7035, light gray, metric cable entry knockouts top, bottom and in the back plate, push-through cable entry diaphragm, 2 protective caps to protect the push-through membrane, indicator light L-. can be mounted in base knock-out M20/M25, for T3-../Z switch, 1-2 contact units

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

Insulated enclosure, HxWxD=160x100x100mm, for T3-2Small enclosure, degree of protection IP65, glass-fiber reinforced polycarbonate, enclosure base RAL 9005, black/operator only RAL 7035, light gray, metric cable entry knockouts top, bottom and in the back plate, push-through cable entry diaphragm, 2 protective caps to protect the push-through membrane, indicator light L-. can be mounted in base knock-out M20/M25, for T3-../Z switch, 1-2 contact units

General specificationsProduct nameEaton Moeller® series CI-K Insulated enclosurePart

no.CI-K2-T3-2EAN4015082074371Product Length/Depth181 millimetreProduct height84 millimetreProduct width100 millimetreProduct weight0.33 kilogramCertificationsIEC/EN 60947-3

CSA-C22.2 No. 94

CE

CSA-C22.2 No. 14-05

UL File No.: E54120

CSA File No.: 012528

UL 508

UL

CSA Class No.: 3211-07

CSA

UL Category Control No.: MITW2Product TradenameCI-KProduct TypeInsulated enclosureProduct Sub TypeNoneCatalog

Notes1 contact unit = 2 contacts

The membrane can be pushed through with the cable: main power cable = 12 - 16 mm, control current cable = 8 mmFeatures & FunctionsEnclosure materialPlasticFitted with:Additional terminal

Push-through cable entry diaphragmGeneral informationDegree of protectionIP65

NEMA 12ModelSurface mountingTypeInsulated enclosureUsed withwith an additional PE clampClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max40 °CDesign verificationEquipment heat dissipation, current-depe...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K2-T3-2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.