

INDUSTRIAL COMPONENT DATA

CI-K2H-100-TS 229304 Y7-229304 EATON ELECTRIC Insulated enclosure, HxWxD 160x100x100mm, +mounting rail

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K2H-100-TS



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K2H-100-TS
Catalog number	Y7-229304
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-57D0608A2D
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=160x100x100mm, +mounting rail

CI-K2H-100-TS

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=160x100x100mm, +mounting rail CI-K2H-100-TS

Insulated enclosure, With mounting rail to IEC/EN 60715, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fiber reinforced polycarbonate, Color: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 100 mm, Height: 160 mm, Depth: 100 mm, Mounting depth for mounting rail 7.5 mm height: 73 mm , Standards: IEC/EN 60529, DIN EN 62208

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton Moeller® series CI-K Insulated enclosure Catalog Number 229304 Model Code CI-K2H-100-TS EAN 4015082293048 Product Length/Depth 181 mm Product Height 100 mm Product Width 100 mm Product Weight 0.32 kg

Certifications UL94: VO/1.5 mm thickness

DIN EN 62208

IEC 60068-2-11

IEC/EN 60529

UL94: HB Catalog Notes Lamp indicator L-... can be mounted in base knock-out M20/M25 Features & Functions

Enclosure color Black (RAL 9005)

Light gray, Operator (RAL 7035)

Light gray, Cover (RAL 7035) Enclosure material Plastic

1 ? x 10¹³ (Surface resistance to IEC 60093) Features Halogen free

UV resistance beneath protective shield Fitted with: Mounting rail to IEC/EN 60715

Control cable entry Knockouts Hard knockout version

Metric cable entry knockouts at the top, bottom and back plate General

Cover material Glass-fiber reinforced polycarbonate Degree of protection IP65

NEMA Other Degree of protection (front side) IP65 Dielectric strength 30 kV/mm, according to IEC 60243-1 Flammability characteristics 650 °C/1 mm thick (push-through membrane and seal material) to VDE 0471 Part 2)

960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2) Model Surface mounting Mounting depth 73 mm

Mounting weight capacity - max 0.7 kg Product category Empty enclosures Suitable for Emergency stop Surface treatment

Resistant to corrosion Track resistance CTI 175 (base, to IEC 60112)

CTI 175 (cover, to IEC 60112) Type Basic enclosure Water consumption 0.29 % (According t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K2H-100-TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.