

INDUSTRIAL COMPONENT DATA

CI-K2H-145-AD 229308 Y7-229308 EATON ELECTRIC Insulated enclosure, HxWxD 160x100x145mm, +component adapter D..

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K2H-145-AD



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K2H-145-AD
Catalog number	Y7-229308
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-A6552A8AF3
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=160x100x145mm, +component adapter DILE+ZE

CI-K2H-145-AD

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=160x100x145mm, +component adapter DILE+ZE CI-K2H-145-AD Insulated enclosure, with adapter plate for contactors DILE with motor-protective relay ZE, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fiber reinforced polycarbonate, Color: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 100 mm, Height: 160 mm, Depth: 145 mm , Mounting depth with mounting plate: 124 mm, Standards: IEC/EN 60529, DIN EN 62208

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series CI-K Insulated enclosure Catalog Number 229308 Model Code CI-K2H-145-AD EAN 4015082293086 Product Length/Depth 181 mm Product Height 145 mm Product Width 100 mm Product Weight 0.46 kg

Certifications UL94: HB

IEC 60068-2-11

IEC/EN 60529

UL94: VO/1.5 mm thickness

DIN EN 62208 Catalog Notes Lamp indicator L-... can be mounted in base knock-out M20/M25 Product specifications

Type Basic enclosure Features Halogen free

UV resistance beneath protective shield 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K2H-145-AD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.