

INDUSTRIAL COMPONENT DATA

CI-K2-100-M 206893 Y7-206893 EATON ELECTRIC Insulated enclosure, HxWxD 160x100x100mm, +mounting plate

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K2-100-M



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K2-100-M
Catalog number	Y7-206893
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-750596F5E6
Generated	2026-08-05

Product Overview

Insulated enclosure, HxWxD=160x100x100mm, +mounting plate

CI-K2-100-M

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=160x100x100mm, +mounting plate CI-K2-100-M

Insulated enclosure, With mounting plate, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fiber reinforced polycarbonate, Color: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: Push-through cable entry diaphragm, Dimensions Width: 100 mm, Height: 160 mm, Depth: 100 mm, Mounting depth with mounting plate: 79 mm, Standards: IEC/EN 60529 , DIN EN 62208

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton Moeller® series CI-K Insulated enclosure Catalog Number 206893 Model Code CI-K2-100-M EAN 4015082068936 Product Length/Depth 181 mm Product Height 100 mm Product Width 100 mm Product Weight 0.498 kg

Certifications IEC 60068-2-11

UL94: VO/1.5 mm thickness

UL94: HB

IEC/EN 60529

DIN EN 62208 Catalog Notes Lamp indicator L-... can be mounted in base knock-out M20/M25 Features & Functions

Enclosure color Light gray, Cover (RAL 7035)

Light gray, Operator (RAL 7035)

Black (RAL 9005) Enclosure material Plastic

1 ? x 10¹³ (Surface resistance to IEC 60093) Features Halogen free

UV resistance beneath protective shield Fitted with: Control cable entry

Mounting plate Knockouts Metric cable entry knockouts at the top, bottom and back plate

Push-through cable entry diaphragm General

Cover material Glass-fiber reinforced polycarbonate Degree of protection IP65

NEMA Other Degree of protection (front side) IP65 Dielectric strength 30 kV/mm, according to IEC 60243-1 Flammability characteristics 960 °C/1 mm thickness (base, cover; glow wire to VDE 0471 Part 2)

650 °C/1 mm thick (push-through membrane and seal material) to VDE 0471 Part 2) Model Surface mounting Mounting

depth 79 mm Mounting weight capacity - max 0.7 kg Product category Empty enclosures Suitable for Emergency stop

Surface treatment Resistant to corrosion Track resistance CTI 175 (base, to IEC 60112)

CTI 175 (cover, to IEC 60112) Type Basic enclosure Water consumption 0.29 % (According to D...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K2-100-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.