

INDUSTRIAL COMPONENT DATA

CI-K3-125-TS 206884 Y7-206884 EATON ELECTRIC Insulated enclosure, HxWxD 200x120x125mm, +mounting rail

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K3-125-TS



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K3-125-TS
Catalog number	Y7-206884
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-EC51F81FC0
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=200x120x125mm, +mounting rail

CI-K3-125-TS

Eaton Moeller® series CI-K Insulated enclosure, HxWxD=200x120x125mm, +mounting rail

Insulated enclosure, With mounting rail to IEC/EN 60715, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fiber reinforced polycarbonate, Color: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 120 mm, Height: 200 mm, Depth: 125 mm, Mounting depth for mounting rail 7.5 mm height: 93 mm , Standards: IEC/EN 60529, DIN EN 62208

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series CI-K Insulated enclosure Catalog Number 206884 Model Code CI-K3-125-TS EAN 4015082068844 Product Length/Depth 222 mm Product Height 125 mm Product Width 120 mm Product Weight 0.61 kg

Certifications DIN EN 62208

UL94: VO/1.5 mm thickness

IEC/EN 60529

IEC 60068-2-11

UL94: HB Catalog Notes Lamp indicator L-... can be mounted in base knock-out M20/M25 Product specifications

Type Basic enclosure Features UV resistance beneath protective shield

Halogen free 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K3-125-TS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.