

INDUSTRIAL COMPONENT DATA

CI-K4-125-M 206897 Y7-206897 EATON ELECTRIC Insulated enclosure, HxWxD 240x160x125mm, +mounting plate

Brand: EATON - MOELLER | Manufacturer Part Number: CI-K4-125-M



Manufacturer	EATON - MOELLER
MPN / Reference	CI-K4-125-M
Catalog number	Y7-206897
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-C7BB797E22
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=240x160x125mm, +mounting plate

CI-K4-125-M

Insulated enclosure, With mounting plate, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fiber reinforced polycarbonate, Color: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 160 mm, Height: 240 mm, Depth: 125 mm, Mounting depth with mounting plate: 98 mm, Standards: IEC/EN 60529, DIN EN 62208

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

Insulated enclosure, HxWxD=240x160x125mm, +mounting plateInsulated enclosure, With mounting plate, Product range: CI-K small enclosures, Basic enclosures, Single unit, Degree of Protection: Front IP65, IP65, with push-through cable entry, Material: Glass-fiber reinforced polycarbonate, Color: Enclosure base RAL 9005, black, Operator only RAL 7035, light gray, Description: Metric cable entry knockouts top, bottom and in the back plate, Control cable entry, Lamp indicator L-... can be mounted in base knock-out M20/M25, Cable entry: hard knockout version, Dimensions Width: 160 mm, Height: 240 mm, Depth: 125 mm, Mounting depth with mounting plate: 98 mm, Standards: IEC/EN 60529, DIN EN 62208

General specificationsProduct nameEaton Moeller® series CI-K Insulated enclosurePart

no.CI-K4-125-MEAN4015082068974Product Length/Depth240 millimetreProduct height125 millimetreProduct width160

millimetreProduct weight1.01 kilogramCertificationsIEC 60068-2-11

UL94: HB

UL94: VO/1.5 mm thickness

IEC/EN 60529

DIN EN 62208Product TradenameCI-KProduct TypeInsulated enclosureProduct Sub TypeNoneCatalog NotesLamp indicator L-... can be mounted in base knock-out M20/M25Features & FunctionsEnclosure colorBlack (RAL 9005)

Light gray, Cover (RAL 7035)

Light gray, Operator (RAL 7035)Enclosure material1 ? x 10¹³ (Surface resistance to IEC 60093)

PlasticFeaturesUV resistance beneath protective shield

Halogen freeFitted with:Mounting plate

Control cable entryKnockoutsMetric cable entry knockouts at the top, bo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI-K4-125-M with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.