

INDUSTRIAL COMPONENT DATA

NZM1-XCI23-TVD 271522 Y7-271522 EATON ELECTRIC

Insulated enclosure, HxWxD 250x187.5x175mm, for size 1

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XCI23-TVD



Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XCI23-TVD
Catalog number	Y7-271522
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-41BEA3CC2C
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=250x187.5x175mm, for size 1

NZM1-XCI23-TVD

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=250x187.5x175mm, for NZM size 2, TVD

Insulated housing Ci, protection category IP65, HxWxD=250x187.5x175mm, for NZM size 1, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle included, pre-drilled mounting plate for breaker and optional PE/N clamps, housing cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci MCCB enclosure Catalog Number 271522 Model Code NZM1-XCI23-TVD EAN 4015082715229 Product Length/Depth 175 mm Product Height 250 mm Product Width 187.5 mm Product Weight 2.614 kg
Compliances IEC

RoHS conform Product specifications

Special features With door coupling rotary handle Complete with all required functional parts Type xEnergy Safety Ci Fitted with: Transparent cover

Standard, black/gray Frame NZM1 Enclosure CI23-150 Used with NZM1, PN1, N(S)1

xEnergy Safety Ci Accessory/spare part type Others Degree of protection IP65
Other Enclosure material Plastic Rated uninterrupted current (Iu) at max. cross section 63 A Terminal for retrofitting of 5th conductor (neutral conductor) K50/1 Locking facility Lockable on the 0 position on the handle using up to 3 padlocks. Additionally with cover interlock. Model Surface mounting Number of poles Three-pole
ETIM for 271522 Low-voltage industrial controls and switchgear (EC000712)
Feature Name
Feature Value
Housing material (EF001596)
Plastic
Width (EF000008)
187.5 mm
Height (EF000040)
250 mm
Depth (EF000049)
175 mm
With transparent cover (EF001094)
Yes
Suitable for emergency stop (EF001433)
No
Model (EF000010)
Surface mounting
Degree of protection (IP) (EF005474)
IP65
Degree of protection (NEMA) (EF011959)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XCI23-TVD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.