

INDUSTRIAL COMPONENT DATA

NZM1-XCI43/2-TVDVR 104646 Y7-104646 EATON ELECTRIC

Insulated enclosure, HxWxD 375x250x225mm, for size 1

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XCI43/2-TVDVR



Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XCI43/2-TVDVR
Catalog number	Y7-104646
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-1751133241
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=375x250x225mm, for size 1

NZM1-XCI43/2-TVDVR

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=375x250x225mm, for NZM size 1, TVDR

Insulated enclosure Ci, degree of protection IP65, HxWxD=375x250x225mm, for NZM size 1, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle red/yellow included, pre-drilled mounting plate for breaker and optional PE/N clamps, enclosure cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges and cable grommets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci LV systems LV switchgear Catalog Number 104646 Model Code

NZM1-XCI43/2-TVDVR EAN 4015081044566 Product Length/Depth 225 mm Product Height 375 mm Product Width 250 mm Product Weight 4.283 kg Compliances IEC

RoHS conform Product specifications

Special features With door coupling rotary handle Complete with all required functional parts Type xEnergy Safety Ci Fitted with: Transparent cover

Red-yellow for emergency switching off Frame NZM1 Enclosure CI43-200 Used with NZM1(-4), PN1(-4), N(S)1(-4)

xEnergy Safety Ci Accessory/spare part type Others Degree of protection Other
IP65 Enclosure material Plastic Rated uninterrupted current (Iu) at max. cross section <= 160 A Terminal for retrofitting of
5th conductor (neutral conductor) K50/1, K95/1N/BR Locking facility Lockable in the 0 position using up to 3 padlocks on the
handle and/or switch each. Additionally with cover interlock. Model Surface mounting Number of poles Three-pole/Four-pole
Suitable for Emergency stop
ETIM for 104646 Low-voltage industrial controls and switchgear (EC000712)
Feature Name
Feature Value
Housing material (EF001596)
Plastic
Width (EF000008)
250 mm
Height (EF000040)
375 mm
Depth (EF000049)
225 mm
With transparent cover (EF001094)
true
Suitable for emergency stop (EF001433)
true
Model (EF000010)
Surface mounting
Degree of protection (IP) (EF005474)
Other
Degree of protection (NEMA) (EF011959)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XCI43/2-TVDVR with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.