

INDUSTRIAL COMPONENT DATA

NZM1-XCI43-TVD 271523 Y7-271523 EATON ELECTRIC

Insulated enclosure, HxWxD 495x250x248.5mm, for NZM size 1

Brand: EATON - MOELLER | Manufacturer Part Number: NZM1-XCI43-TVD



Manufacturer	EATON - MOELLER
MPN / Reference	NZM1-XCI43-TVD
Catalog number	Y7-271523
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-39A226D53D
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=495x250x248.5mm, for NZM size 1

NZM1-XCI43-TVD

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=375x250x175mm, for NZM size 2, TVD

Insulated enclosure Ci, degree of protection IP65, HxWxD=375x250x175mm, for NZM size 1, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle black included, pre-drilled mounting plate for breaker and optional PE/N clamps, enclosure cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges and cable grommets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci MCCB enclosure Catalog Number 271523 Model Code NZM1-XCI43-TVD EAN 4015082715236 Product Length/Depth 175 mm Product Height 375 mm Product Width 250 mm Product Weight 5.681 kg

Compliances IEC

RoHS conform Product specifications

Used with NZM1(-4), PN1(-4), N(S)1(-4)

xEnergy Safety Ci Special features With door coupling rotary handle Complete with all required functional parts Type
xEnergy Safety Ci Fitted with: Transparent cover
Standard, black/gray Frame NZM1 Enclosure CI43-150 Accessory/spare part type Others Degree of protection IP65
Other Enclosure material Plastic Rated uninterrupted current (Iu) at max. cross section 125 A Terminal for retrofitting of 5th
conductor (neutral conductor) K50/1, K95/1N/BR Locking facility Lockable on the 0 position on the handle using up to 3
padlocks. Additionally with cover interlock. Model Surface mounting Number of poles Three-pole/Four-pole
ETIM for 271523 Low-voltage industrial controls and switchgear (EC000712)

Feature Name

Feature Value

Housing material (EF001596)

Plastic

Width (EF000008)

250 mm

Height (EF000040)

375 mm

Depth (EF000049)

175 mm

With transparent cover (EF001094)

Yes

Suitable for emergency stop (EF001433)

No

Model (EF000010)

Surface mounting

Degree of protection (IP) (EF005474)

IP65

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM1-XCI43-TVD with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.