

INDUSTRIAL COMPONENT DATA

NZM2-XCI43-TVDVR 271529 Y7-271529 EATON ELECTRIC

Insulated enclosure, HxWxD 375x250x225mm, for size 2

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2-XCI43-TVDVR



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2-XCI43-TVDVR
Catalog number	Y7-271529
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-F162EE0983
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=375x250x225mm, for size 2

NZM2-XCI43-TVDVR

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=375x250x225mm, for NZM size 3, TVDR

Insulated enclosure Ci, degree of protection IP65, HxWxD=375x250x225mm, for NZM size 2, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle red/yellow included, pre-drilled mounting plate for breaker and optional PE/N clamps, enclosure cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges and cable grommets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci MCCB enclosure Catalog Number 271529 Model Code NZM2-XCI43-TVDVR EAN 4015082715298 Product Length/Depth 225 mm Product Height 375 mm Product Width 250 mm Product Weight 6.296 kg

Compliances IEC

RoHS conform Product specifications

Used with xEnergy Safety Ci

NZM2(-4), PN2(-4), N(S)2(-4) Special features With door coupling rotary handle Complete with all required functional parts

Type xEnergy Safety Ci Fitted with: Transparent cover

Red-yellow for emergency switching off Frame NZM2 Enclosure CI43-200 Accessory/spare part type Others Degree of protection IP65

Other Enclosure material Plastic Rated uninterrupted current (Iu) at max. cross section ≤ 200 A Terminal for retrofitting of 5th conductor (neutral conductor) K50/1, K95/1N/BR, K150/1/BR, K240/1/BR Locking facility Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock. Model Surface mounting Number of poles Three-pole/Four-pole Suitable for Emergency stop

ETIM for 271529 Low-voltage industrial controls and switchgear (EC000712)

Feature Name

Feature Value

Housing material (EF001596)

Plastic

Width (EF000008)

250 mm

Height (EF000040)

375 mm

Depth (EF000049)

225 mm

With transparent cover (EF001094)

Yes

Suitable for emergency stop (EF001433)

Yes

Model (EF000010)

Surface mounting

Degree of protection (IP) (EF005474)

IP65

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2-XCI43-TVDVR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.