

INDUSTRIAL COMPONENT DATA

NZM2-XCI45-TVDVR 279356 Y7-279356 EATON ELECTRIC

Insulated enclosure, HxWxD 500x250x225mm, for NZM size 2

Brand: EATON - MOELLER | Manufacturer Part Number: NZM2-XCI45-TVDVR



Manufacturer	EATON - MOELLER
MPN / Reference	NZM2-XCI45-TVDVR
Catalog number	Y7-279356
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-335C4B0289
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=500x250x225mm, for NZM size 2

NZM2-XCI45-TVDVR

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=500x375x225mm, for NZM size 2, TVDR

Insulated enclosure Ci, degree of protection IP65, HxWxD=500x375x225mm, for NZM size 2, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle red/yellow included, pre-drilled mounting plate for breaker and optional PE/N clamps, enclosure cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges and cable grommets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci MCCB enclosure Catalog Number 279356 Model Code NZM2-XCI45-TVDVR EAN 4015082793562 Product Length/Depth 225 mm Product Height 500 mm Product Width 375 mm Product Weight 10.32 kg

Compliances IEC

RoHS conform Product specifications

Used with xEnergy Safety Ci

NZM2(-4), PN2(-4), N(S)2(-4) Special features With door coupling rotary handleComplete with all required functional parts

Type xEnergy Safety Ci Fitted with: Transparent cover

Red-yellow for emergency switching off Frame NZM2 Enclosure CI45-200 Accessory/spare part type Others Degree of protection IP65

Other Enclosure material Plastic Rated uninterrupted current (Iu) at max. cross section 250 A Terminal for retrofitting of 5th conductor (neutral conductor) K50/1, K95/1N/BR, K150/1/BR, K240/1/BR Locking facility Lockable in the 0 position using up to 3 padlocks on the handle and/or switch each. Additionally with cover interlock. Model Surface mounting Number of poles Three-pole/Four-pole Suitable for Emergency stop

ETIM for 279356 Low-voltage industrial controls and switchgear (EC000712)

Feature Name

Feature Value

Housing material (EF001596)

Plastic

Width (EF000008)

375 mm

Height (EF000040)

500 mm

Depth (EF000049)

225 mm

With transparent cover (EF001094)

Yes

Suitable for emergency stop (EF001433)

Yes

Model (EF000010)

Surface mounting

Degree of protection (IP) (EF005474)

IP65

Degree of protection (NEMA) (EF011959)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM2-XCI45-TVDVR with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.