

INDUSTRIAL COMPONENT DATA

NZM3-XCI48-TVD 271525 Y7-271525 EATON ELECTRIC

Insulated enclosure, HxWxD 750x250x275mm, for size 3

Brand: EATON - MOELLER | Manufacturer Part Number: NZM3-XCI48-TVD



Manufacturer	EATON - MOELLER
MPN / Reference	NZM3-XCI48-TVD
Catalog number	Y7-271525
Category	Empty enclosure for switchgear
Minimum order	1 Pcs
Document ID	EO-FFBE527EA0
Generated	2026-08-06

Product Overview

Insulated enclosure, HxWxD=750x250x275mm, for size 3

NZM3-XCI48-TVD

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, box size HxWxD=750x375x275mm, for NZM size 4, TVD

Insulated enclosure Ci, degree of protection IP65, HxWxD=750x375x275mm, for NZM size 3, protection class 2, impact-resistant polycarbonate, door-coupling rotary breaker handle black included, pre-drilled mounting plate for breaker and optional PE/N clamps, enclosure cap prepared for rotary handle, transparent smoky gray cap, wall-mounting lugs, includes top and bottom cable insertion flanges and cable grommets.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers NZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci MCCB enclosure Catalog Number 271525 Model Code NZM3-XCI48-TVD EAN 4015082715250 Product Length/Depth 275 mm Product Height 750 mm Product Width 375 mm Product Weight 13.539 kg
Compliances IEC

RoHS conform Product specifications

Special features With door coupling rotary handle Complete with all required functional parts Type xEnergy Safety Ci Fitted with: Standard, black/gray

Transparent cover Frame NZM3 Enclosure CI48-250 Used with xEnergy Safety Ci

NZM3(-4), PN3(-4), N(S)3(-4) Accessory/spare part type Others Degree of protection IP65
Other Enclosure material Plastic Rated uninterrupted current (Iu) at max. cross section ≤ 400 A Terminal for retrofitting of 5th conductor (neutral conductor) K95/1N/BR, K150/1/BR, K240/1/BR, K2X240/1/BR Locking facility Lockable on the 0 position on the handle using up to 3 padlocks. Additionally with cover interlock. Model Surface mounting Number of poles Three-pole/Four-pole
ETIM for 271525 Low-voltage industrial controls and switchgear (EC000712)
Feature Name
Feature Value
Housing material (EF001596)
Plastic
Width (EF000008)
375 mm
Height (EF000040)
750 mm
Depth (EF000049)
275 mm
With transparent cover (EF001094)
Yes
Suitable for emergency stop (EF001433)
No
Model (EF000010)
Surface mounting
Degree of protection (IP) (EF005474)
IP65
Degree of protection (NEMA) (EF011959)
Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NZM3-XCI48-TVD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.