

INDUSTRIAL COMPONENT DATA

CI43E-125 093133 Y7-93133 EATON ELECTRIC Insulated enclosure, +knockouts, HxWxD 250x375x150mm

Brand: EATON - MOELLER | Manufacturer Part Number: CI43E-125



Manufacturer	EATON - MOELLER
MPN / Reference	CI43E-125
Catalog number	Y7-93133
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-FEA6C464B4
Generated	2026-08-06

Product Overview

Insulated enclosure, +knockouts, HxWxD=250x375x150mm

Insulating Enclosure With Metric Pre-Drills HxWxD=250x375x150mm

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, +knockouts, HxWxD=250x375x150mm

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=2xM50/32 and 6xM25/16 and 8xM20, each side=1xM50/32 and 6xM25/16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7035, grey (base), transparent smoky, (cover), mounting depth with mounting plate=125mm, cover type: transparent smoky , base type: knockout cover is optionally fitted by user with cylinder lock DVZ...-CI.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci empty enclosure insulated Catalog Number 093133 Model Code CI43E-125 EAN 4015080931331 Product Length/Depth 150 mm Product Height 250 mm Product Width 375 mm Product Weight 1.981 kg Compliances RoHS conform Certifications EN 62208

EN 61439-2 Product specifications

Used with Eaton Switching and protection devices Special features Type Basic enclosure

Individual enclosures

xEnergy Safety Ci

Features UV resistance beneath protective shield

Cover with overpressure release 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. 10.13 Mechanical function Meets the product standard's requirements. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Lower part: 960 °C / cover: 850 °C 10.2.4 Resistance to ultra-violet (UV) radiation Not relevant to indoor installations. 10.2.5 Lifting 10 kg per enclosure with support frame and lifting aid met; assembled and secured as per the late...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI43E-125 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.