

INDUSTRIAL COMPONENT DATA

CI44E-150 033809 Y7-33809 EATON ELECTRIC Insulated enclosure, +knockouts, HxWxD 375x375x175mm

Brand: EATON - MOELLER | Manufacturer Part Number: CI44E-150



Manufacturer	EATON - MOELLER
MPN / Reference	CI44E-150
Catalog number	Y7-33809
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-C744D3CEFA
Generated	2026-08-06

Product Overview

Insulated enclosure, +knockouts, HxWxD=375x375x175mm

Insulating Enclosure With Metric Pre-Drills HxWxD=375x375x175mm

Eaton xEnergy Safety Ci LV systems LV switchgear. Insulated enclosure, +knockouts, HxWxD=375x375x175mm

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=1xM50/32 and 2xM40/25 and 8xM25/16 and 2xM20, each side=1xM63/40 and 6xM25/16 and 10xM20 and 2xM16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7035, grey (base), transparent smoky, (cover), mounting depth with mounting plate=150mm , cover type: transparent smoky, base type: knockout cover is optionally fitted by user with cylinder lock DVZ...-CI.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Insulating Enclosures

Additional Product Information

General specifications

Product Name Eaton xEnergy Safety Ci empty enclosure insulated Catalog Number 033809 Model Code CI44E-150 EAN 4015080338093 Product Length/Depth 175 mm Product Height 375 mm Product Width 375 mm Product Weight 2.818 kg Compliances RoHS conform Certifications EN 61439-2

EN 62208 Product specifications

Special features With metric knockouts in all sides of the enclosure Include fixing straps for wall mounting Sealable cover

fasteners Full-area knockouts in the side can be converted to a distribution board enclosure Integrated pressure-relief mechanism for short-circuits Type Basic enclosure Individual enclosures x Energy Safety Ci Features UV resistance beneath protective shield

Cover with overpressure release 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. 10.13 Mechanical function Meets the product standard's requirements. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Lower part: 960 °C / cover: 850 °...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI44E-150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.