

INDUSTRIAL COMPONENT DATA

CI23E-125-RAL7032 090152 EATON ELECTRIC Insulated enclosure, +knockouts, RAL7032, HxWxD 250x187.5x150mm

Brand: EATON - MOELLER | Manufacturer Part Number: CI23E-125-RAL7032



Manufacturer	EATON - MOELLER
MPN / Reference	CI23E-125-RAL7032
Catalog number	090152
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-4E3BC11C35
Generated	2026-08-06

Product Overview

Insulated enclosure, +knockouts, RAL7032, HxWxD=250x187.5x150mm

Box of insulating material; With fixing guide holes metric; RAL7032; HxWxD=250x187.5x150mm

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=1xM32/20 and 6xM20 and 2xM16, each side=2xM32/20 and 4xM25/16 and 4xM20 and 4xM16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7032, pebble grey (base), RAL 7032, pebble grey (cover), mounting depth with mounting plate=125mm , cover type: non-transparent, lower section type: knockout cover is optionally fitted by user with cylinder lock DVZ...-CI.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

circuit limiter, low voltage, 125 A, AC 125 V, DC 80 V, 22.2 x 81 mm, UL, very fast acting Fuse, circuit limiter, low voltage, 125 A, AC 125 V, DC 80 V, 22.2 x 81 mm, UL, very fast acting, UL, Breaking Capacity 2.5 kA, Optional accessories fuse-block 4164, Supplied with [Delivery program

Product range Fuse Basic function circuit limiter Field of application low voltage Rated current [I] 125 A Rated voltage AC 125 V

DC 80 V Size 22.2 x 81 mm Breaking Capacity 2.5 kA Release characteristic [class] very fast acting Standard/Approval UL Standards/Regulations UL Optional accessories fuse-block 4164 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 125 A Rated voltage 80 V Voltage type AC/DC Rated switching capacity 2.5 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No] ETIM for 090152 Distribution boards (EC000058)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounted

Type of covering (EF000339)

None

Cover model (EF009212)

Closed

Type of door (EF004464)

None

Transparent cover/door (EF006244)

No

With lock (EF006306)

No

Nominal current (In) (EF008873)

1600 A

Height (EF000040)

250 mm

Width (EF000008)

187.5 mm

Depth (EF000049)

150 mm

Built-in depth (EF000218...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI23E-125-RAL7032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.