

INDUSTRIAL COMPONENT DATA

CI23E-150-RAL7032 090153 2502332 EATON ELECTRIC

Insulated enclosure, +knockouts, RAL7032, HxWxD 250x187.5x17..

Brand: EATON - MOELLER | Manufacturer Part Number: CI23E-150-RAL7032



Manufacturer	EATON - MOELLER
MPN / Reference	CI23E-150-RAL7032
Catalog number	2502332
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-30582A7F59
Generated	2026-08-06

Product Overview

Insulated enclosure, +knockouts, RAL7032, HxWxD=250x187.5x175mm

Insulating box; With metric pre-drills; RAL7032; HxWxD=250x187.5x175mm

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=1xM32/20 and 6xM20 and 2xM16, each side=2xM32/20 and 4xM25/16 and 4xM20 and 4xM16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7032, pebble grey (base), RAL 7032, pebble grey (cover), mounting depth with mounting plate=150mm , cover type: non-transparent, lower section type: knockout cover is optionally fitted by user with cylinder lock DVZ...-CI.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Insulating Enclosures**

Additional Product Information

Fuse-link, High speed, 150 A, AC 600 V, 38.1 x 131 mm, UR Fuse, Fuse-link, High speed, 150 A, AC 600 V, 38.1 x 131 mm, UR, breaking capacity 200 kA, supplied for replacement only, use 700 V FWP for new installations [Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 150 A Rated voltage 600 V Voltage type AC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No]

ETIM for 090153 Distribution boards (EC000058)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounted

Type of covering (EF000339)

None

Cover model (EF009212)

Closed

Type of door (EF004464)

None

Transparent cover/door (EF006244)

No

With lock (EF006306)

No

Nominal current (In) (EF008873)

1600 A

Height (EF000040)

250 mm

Width (EF000008)

187.5 mm

Depth (EF000049)

175 mm

Built-in depth (EF000218)

150 mm

Inner depth (EF001131)

150 mm

Material plate thickness cabinet (EF009170)

6 mm

Material plate thickness door/cover (EF009171)

6 mm

RAL-number (EF000116)

7032

Number of modules (EF004427)

1

Number of rows (EF000266)

0

Width in number of modular spacings (EF002950)

9

Number of openings for flange plates (EF009554)

4

Extension possible (EF001088)

Yes

Number of conduit inlets (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI23E-150-RAL7032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.