

INDUSTRIAL COMPONENT DATA

CI43E-125-RAL7032 090154 EATON ELECTRIC Insulated enclosure, +knockouts, RAL7032, HxWxD 250x375x150mm

Brand: EATON - MOELLER | Manufacturer Part Number: CI43E-125-RAL7032



Manufacturer	EATON - MOELLER
MPN / Reference	CI43E-125-RAL7032
Catalog number	090154
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-F7DB1D5588
Generated	2026-08-06

Product Overview

Insulated enclosure, +knockouts, RAL7032, HxWxD=250x375x150mm

Box of insulating material; With fixing guide holes metric; RAL7032; HxWxD=250x375x150mm

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=2xM50/32 and 6xM25/16 and 8xM20, each side=1xM50/32 and 6xM25/16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7032, pebble grey (base), RAL 7032, pebble grey (cover), mounting depth with mounting plate=125mm, cover type: non-transparent , lower section type: knockout cover is optionally fitted by user with cylinder lock DVZ...-CI.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

Fuse-link, low voltage, 125 A, AC 300 V, DC 160 V, 61.9 x 22.2, T, UL, very fast acting Fuse, Fuse-link, low voltage, 125 A, AC 300 V, DC 160 V, 61.9 x 22.2, T, UL, very fast acting, Breaking Capacity 200 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 125 A Rated voltage DC 160 V Size 61.9 x 22.2 Utilization category T Breaking Capacity 20 kA Release characteristic [class] very fast acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 125 A Rated voltage 300 V Voltage type AC/DC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No] ETIM for 090154 Distribution boards (EC000058)

Feature Name

Feature Value

Mounting method (EF000003)

Surface mounted

Type of covering (EF000339)

Optional

Cover model (EF009212)

Closed

Type of door (EF004464)

None

Transparent cover/door (EF006244)

No

With lock (EF006306)

No

Nominal current (In) (EF008873)

1600 A

Height (EF000040)

250 mm

Width (EF000008)

375 mm

Depth (EF000049)

150 mm

Built-in depth (EF000218)

125 mm

Inner depth (EF001131)

125 mm

Material plate thickness cabinet (EF009170)

6 mm

Material plate thickness do...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI43E-125-RAL7032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.