

INDUSTRIAL COMPONENT DATA

CI44E-200-RAL7032 090159 EATON ELECTRIC Insulated enclosure, +knockouts, RAL7032, HxWxD 375x375x225mm

Brand: EATON - MOELLER | Manufacturer Part Number: CI44E-200-RAL7032



Manufacturer	EATON - MOELLER
MPN / Reference	CI44E-200-RAL7032
Catalog number	090159
Category	Empty cabinet
Minimum order	1 Pcs
Document ID	EO-7C0B2F4E2D
Generated	2026-08-06

Product Overview

Insulated enclosure, +knockouts, RAL7032, HxWxD=375x375x225mm

Box of insulating material; With fixing guide holes metric; RAL7032; HxWxD=375x375x225mm

Individual basic enclosure, material characteristic polycarbonate, impact-resistant, degree of protection IP65, patented cover fasteners with integrated overpressure compensation, with metric cable entry knockouts in all side walls, cable entries top and bottom, each=1xM50/32 and 2xM40/25 and 8xM25/16 and 2xM20, each side=1xM63/40 and 6xM25/16 and 10xM20 and 2xM16, fixing straps for wall fixing, sealable cover fasteners, full-area knockouts in the sides can be converted to a distribution board enclosure by knocking out the side walls., RAL 7032, pebble grey (base), RAL 7032, pebble grey (cover), mounting depth with mounting plate=200mm , cover type: non-transparent, lower section type: knockout cover is optionally fitted by user with cylinder lock DVZ...-CI.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Insulating Enclosures
--------------	---

Additional Product Information

Fuse-link, LV, 200 A, AC 600 V, 38 x 146 mm, J, UL, fast acting Fuse, fuse-link, low voltage, 200 A, AC 600 V, 38 x 146 mm, Class J, UL, fast acting, ideal for critical industrial or commercial applications that have specific current limitation requirements. Breaking capacity 200 kA [Delivery program

Product range Fuse Basic function Fuse-link Field of application low voltage Rated current [I] 200 A Rated voltage AC 600 V Size 38 x 146 mm Utilization category J Breaking Capacity 200 kA usable for size/applications ideal for critical industrial or commercial applications that have specific current limitation requirements Release characteristic [class] fast-acting Standard/Approval UL , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 200 A Rated voltage 600 V Voltage type AC Rated switching capacity 200 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No] ETIM for 090159 Distribution boards (EC000058)

Feature Name

Feature Value

Transparent cover/door (EF006244)

No

With lock (EF006306)

No

Height (EF000040)

375 mm

Width (EF000008)

375 mm

Depth (EF000049)

225 mm

Built-in depth (EF000218)

200 mm

RAL-number (EF000116)

7032

Extension possible (EF001088)

Yes

Housing material....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / CI44E-200-RAL7032 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.