

INDUSTRIAL COMPONENT DATA

XT-RJ45-ETH-RS232 289170 Y7-289170 EATON ELECTRIC

Interface switch for XC200 (separates combined RS232/ETH O..

Brand: EATON - MOELLER | Manufacturer Part Number: XT-RJ45-ETH-RS232



Manufacturer	EATON - MOELLER
MPN / Reference	XT-RJ45-ETH-RS232
Catalog number	Y7-289170
Category	Accessories/spare parts for controls
Minimum order	1 Pcs
Document ID	EO-710980EFB6
Generated	2026-08-04

Product Overview

Interface switch for XC200 (separates combined RS232/ETH on 2 RJ45 sockets)

XT-RJ45-ETH-RS232

Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. a particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > XC Modular PLC**

Additional Product Information

General specifications

Product Name Eaton XT Accessory Interface switch Catalog Number 289170 Model Code XT-RJ45-ETH-RS232 EAN 4015082891701 Product Length/Depth 30 mm Product Height 90 mm Product Width 35 mm Product Weight 0.11 kg

Compliances CE Marked Certifications EN 60947-5

CSA Std. C22.2 No. 14-05

UL 508

IEC 60947-5

CSA Std. C22.2 No. 94-91

VDE

CE

UL508

CSA Class No.: 2252-01

CSA-C22.2 No. 142-M

UL

UL Category Control No.: NRAQ

CSA File No.: 012528

CSA

CSA-C22.2 No. 0-M

UL File No.: E135462 General

Connection Connection cable EASY-NT-30/80/150 usable for connection to XC200 Degree of protection IP20 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole,

current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation,

non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal

heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product sta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XT-RJ45-ETH-RS232 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.