

INDUSTRIAL COMPONENT DATA

MVDILE 010113 Y7-10113 EATON ELECTRIC Interlock, mechanical for reversing contactor, DILE

Brand: EATON - MOELLER | Manufacturer Part Number: MVDILE



Manufacturer	EATON - MOELLER
MPN / Reference	MVDILE
Catalog number	Y7-10113
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	1 Pcs
Document ID	EO-C77EFF0B09
Generated	2026-08-02

Product Overview

Interlock, mechanical for reversing contactor, DILE

Mechanical interlocking module. For DILE contactors...

Eaton Moeller® series DILE Interlock, mechanical for reversing contactor, DILE

Interlock, Mechanical interlock, Description: For contactors with the same or different magnet system., 0 mm distance between relays., mechanical lifespan 2.5 x 10⁶ Operations., Additional auxiliary contact modules possible., For use with: DILE...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILE Accessory Interlock Catalog Number 010113 Model Code MVDILE EAN 4015080101130 Product Length/Depth 16 mm Product Height 32 mm Product Width 90 mm Product Weight 0.014 kg

Certifications CSA Class No.: 3211-07

UL 508

UL Category Control No.: NKCR2

UL File No.: E29184

CSA File No.: 012528

CSA

CSA-C22.2 No. 14-05

UL Recognized

IEC/EN 60947-4-1

CE General

Accessories Additional auxiliary contact modules possible. Accessory/spare part type Mechanical locking Distance 0 mm distance between relays. Lifespan 2,500,000 mechanical Operations Product category Accessories Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 50 °C Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation
Mee...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / MVDILE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.