

INDUSTRIAL COMPONENT DATA

INX16B3-10W-1 183641 Y7-183641 EATON ELECTRIC

Switch-disconnector, 3 pole, 1000 A, without protection, IEC, ..

Brand: EATON - MOELLER | Manufacturer Part Number: INX16B3-10W-1



Manufacturer	EATON - MOELLER
MPN / Reference	INX16B3-10W-1
Catalog number	Y7-183641
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-4C13AA05A5
Generated	2026-08-03

Product Overview

Switch-disconnector, 3 pole, 1000 A, without protection, IEC, Withdrawable
INX16B3-10W-1

Eaton Moeller series IZMX/INX - ACB. Switch, disconnector, 3 pole, 1000A, without protection, IEC, Withdrawable, 16B3, 10W, 1

Open switch-disconnectors, Switch-disconnector, Number of poles 3 pole, Rated current = rated uninterrupted current 1000 A, Protective function without protection, Standard/Approval IEC, Installation type Withdrawable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX switch-disconnector Catalog Number 183641 Model Code INX16B3-10W-1
EAN 4015081793778 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 27.74
kg Compliances IEC

IEC/EN 60947

RoHS conform

ETIM for 183641 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes
Version as maintenance-/service switch (EF006986)
Yes
Version as safety switch (EF006985)
No
Version as emergency stop installation (EF006959)
No
Version as reversing switch (EF009408)
No
Number of switches (EF005586)
1
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated operating voltage (EF001435)
690 V
Rated permanent current I_u (EF001389)
1000 A
Rated permanent current at AC-23, 400 V (EF011777)
1000 A
Rated permanent current at AC-21, 400 V (EF009165)
0 A
Rated operation power at AC-3, 400 V (EF001364)
0 kW
Rated short-time withstand current I_{cw} (EF007050)
42 kA
Rated operation power at AC-23, 400 V (EF007027)
0 kW
Switching power at 400 V (EF009166)
0 kW
Conditioned rated short-circuit current I_q (EF001444)
88 kA
Number of poles (EF001391)
3
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
2
Motor drive optional (EF007386)
Yes
Motor drive integrated (EF006697)
No
Voltage release optional (EF007491...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / INX16B3-10W-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.