

**INDUSTRIAL COMPONENT DATA**

# INX40B3-40W-1 184063 Y7-184063 EATON ELECTRIC

## Switch-disconnector, 3 pole, 4000 A, without protection, IEC, ..

Brand: EATON - MOELLER | Manufacturer Part Number: INX40B3-40W-1



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | INX40B3-40W-1       |
| Catalog number  | Y7-184063           |
| Category        | Switch disconnector |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-20270A43F7       |
| Generated       | 2026-08-05          |

### Product Overview

Switch-disconnector, 3 pole, 4000 A, without protection, IEC, Withdrawable

INX40B3-40W-1

Eaton Moeller series IZMX/INX - ACB. Switch, disconnector, 3 pole, 4000A, without protection, IEC, Withdrawable, 40B3, 40W, 1

Open switch-disconnectors, Switch-disconnector, Number of poles 3 pole, Rated current = rated uninterrupted current 4000 A, Protective function without protection, Standard/Approval IEC, Installation type Withdrawable

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

### Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX switch-disconnector Catalog Number 184063 Model Code INX40B3-40W-1

EAN 4015081796021 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 69 kg

Compliances IEC

IEC/EN 60947

RoHS conform

ETIM for 184063 Low-voltage industrial controls and switchgear (EC000216)

Feature Name

Feature Value

Version as main switch (EF006981)

Yes  
Version as maintenance-/service switch (EF006986)  
Yes  
Version as safety switch (EF006985)  
No  
Version as emergency stop installation (EF006959)  
No  
Version as reversing switch (EF009408)  
No  
Number of switches (EF005586)  
1  
Max. rated operation voltage  $U_e$  AC (EF007355)  
690 V  
Rated operating voltage (EF001435)  
690 V  
Rated permanent current  $I_u$  (EF001389)  
4000 A  
Rated permanent current at AC-23, 400 V (EF011777)  
4000 A  
Rated permanent current at AC-21, 400 V (EF009165)  
0 A  
Rated operation power at AC-3, 400 V (EF001364)  
0 kW  
Rated short-time withstand current  $I_{cw}$  (EF007050)  
66 kA  
Rated operation power at AC-23, 400 V (EF007027)  
0 kW  
Switching power at 400 V (EF009166)  
0 kW  
Conditioned rated short-circuit current  $I_q$  (EF001444)  
144 kA  
Number of poles (EF001391)  
3  
Number of auxiliary contacts as normally closed contact (EF001377)  
0  
Number of auxiliary contacts as normally open contact (EF001376)  
0  
Number of auxiliary contacts as change-over contact (EF003531)  
2  
Motor drive optional (EF007386)  
Yes  
Motor drive integrated (EF006697)  
No  
Voltage release optional (EF007491)....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / INX40B3-40W-1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.