

INDUSTRIAL COMPONENT DATA

INX40N3-25W-1 184069 0004398431 EATON ELECTRIC
Switch-disconnector, 3 pole, 2500 A, without protection, IEC,...

Brand: EATON - MOELLER | Manufacturer Part Number: INX40N3-25W-1



Manufacturer	EATON - MOELLER
MPN / Reference	INX40N3-25W-1
Catalog number	Y7-184069
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-58C15EEB59
Generated	2026-08-03

Product Overview

Switch-disconnector, 3 pole, 2500 A, without protection, IEC, Withdrawable
INX40N3-25W-1

Open switch-disconnectors, Switch-disconnector, Number of poles 3 pole, Rated current = rated uninterrupted current 2500 A, Protective function without protection, Standard/Approval IEC, Installation type Withdrawable

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

EL-Nummer (Norway)4398431Switch-disconnector, 3 pole, 2500A, without protection, IEC, WithdrawableOpen switch-disconnectors, Switch-disconnector, Number of poles 3 pole, Rated current = rated uninterrupted current 2500 A, Protective function without protection, Standard/Approval IEC, Installation type WithdrawableDelivery program Product rangeAir circuit-breakers/switch-disconnectorsProduct rangeOpen switch-disconnectorsCurrent RangeUp to 4000 AProtective functionwithout protectionInstallation typeWithdrawableCassette must be separately ordered.Construction sizeINX40Release systemwithout releasesStandard/ApprovalIECNumber of poles3 poleDegree of ProtectionIP31 with door seals, IP55 with protective coveroptionally fittable by user with comprehensive accessoriesRated current = rated uninterrupted current [In= Iu]2500 ARated short-circuit making capacity up to 440V/690V 42/42 [Icm]187 kARated short-time withstand current t =1 s [Icw]85 kARated short-time withstand current t =3 s [Icw]66 kATechnical data GeneralStandardsIEC/EN 60947Ambient temperatureStorage [-?] -40 - +70 °CAmbient temperatureAmbient temperature-25 - +70 °CMounting positionUtilization categoryBDegree of ProtectionIP31 with door seals, IP55 with protective coverDirection of incoming supplyas requiredMain conducting pathsRated current = rated uninterrupted current [In= Iu]2500 ARated

uninterrupted current at 50 °C [I_u]2500 A Rated uninterrupted current at 60 °C [I_u]2500 A Rated uninterrupted current at 70 °C [I_u]2500...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / INX40N3-25W-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.