

INDUSTRIAL COMPONENT DATA

E59-M30A115C02-D1 136221 Y7-136221 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 15mm, 4L, 6-48VDC, N..

Brand: EATON - MOELLER | Manufacturer Part Number: E59-M30A115C02-D1



Manufacturer	EATON - MOELLER
MPN / Reference	E59-M30A115C02-D1
Catalog number	Y7-136221
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-F44AD78D98
Generated	2026-08-04

Product Overview

Proximity switch, inductive, 1N/O, Sn=15mm, 4L, 6-48VDC, NPN, PNP, M30, metal

E59-M30A115C02-D1

Proximity switch, Inductive Sensors, Product range: iProx Series, Connection: 3-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: Ue= 6 - 48 V DC, Rated switching distance: Sn= 15 mm, Type of mounting: Flush, Switching type: NPN, PNP, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, IP69K, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

Proximity switch, inductive, 1N/O, Sn=15mm, 4L, 6-48VDC, NPN, PNP, M30, metalProximity switch, Inductive Sensors, Product range: iProx Series, Connection: 3-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: Ue= 6 - 48 V DC, Rated switching distance: Sn= 15 mm, Type of mounting: Flush, Switching type: NPN, PNP, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, IP69K, Standards: IEC/EN 60947-5-2Delivery program

Basic functionInductive SensorsProduct rangeiProx SeriesConnection3-wireDesign (outer dimensions)M30 x 1.5 mmRated operational voltage [Ue]6 - 48 V DCRated switching distance [Sn]15 mmType of mountingFlushSwitching typeNPN PNPFor connection of:2 m connection cableContactsN/O = Normally open1 N/OMaterialStainless steelDegree of ProtectionIP67, IP69Technical data

GeneralStandardsIEC/EN 60947-5-2Ambient temperature-40 - +70Mechanical shock resistance30

Shock duration 11 ms gDegree of ProtectionIP67, IP69CharacteristicsRated switching distanceRated switching distance
[Sn]15 mmRepetition accuracy of Sn1 %Temperature drift of Sn10 %Switching hysteresis of Sn15 %Rated operational
voltage [Ue]6 - 48 V DCMaximum load current [Ie]< 300 mAOperating current in the switched state at 24 V DC [Ib]15
mAVoltage drop at Ie[Ud]2.5 VSwitching Frequency240 HzMin. load current [Ie]1 mAResidual current through the load in
the blocked state at 230 V AC and 24 V DC [Ir]0.15 mASwitching state displayRed LEDOp...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E59-M30A115C02-D1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.