

INDUSTRIAL COMPONENT DATA

E59-M30C129C02-D1 136225 Y7-136225 EATON ELECTRIC Proximity switch, inductive, 1N/O, Sn 29mm, 4L, 6-48VDC, N..

Brand: EATON - MOELLER | Manufacturer Part Number: E59-M30C129C02-D1



Manufacturer	EATON - MOELLER
MPN / Reference	E59-M30C129C02-D1
Catalog number	Y7-136225
Category	Inductive proximity switch
Minimum order	1 Pcs
Document ID	EO-7F91F891F5
Generated	2026-08-01

Product Overview

Proximity switch, inductive, 1N/O, Sn=29mm, 4L, 6-48VDC, NPN, PNP, M30, metal

E59-M30C129C02-D1

Proximity switch, Inductive Sensors, Product range: iProx Series, Connection: 3-wire, Design (outer dimensions): M30 x 1.5 mm, Rated operational voltage: $U_e = 6 - 48 \text{ V DC}$, Rated switching distance: $S_n = 29 \text{ mm}$, Type of mounting: Non-flush, Switching type: NPN, PNP, 2 m connection cable, Contacts N/O = Normally open: 1 N/O, Material: Stainless steel, Degree of Protection: IP67, IP69K, Standards: IEC/EN 60947-5-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Sensors
--------------	---------------------------

Additional Product Information

General specifications

Product Name Eaton E59 AccuProx analog inductive proximity sensor Catalog Number 136225 Model Code

E59-M30C129C02-D1 EAN 4015081330188 Product Length/Depth 152.4 mm Product Height 44.45 mm Product Width 127 mm Product Weight 0.45 kg Certifications CSA-C22.2 No. 14

UL File No.: E166051

UL

UL 508

CE

IEC/EN 60947-5-2

Certified by UL for use in Canada

UL Category Control No.: NRKH, NRKH7

CSA File No.: UL report applies to both US and Canada Product specifications

Type Inductive sensor Electric connection type Cable Enclosure material finishing Other Actuation type Metallic Target
Enclosure material Metal Enclosure type Cylinder, screw-thread Category (EN 954-1) B Explosion safety category for dust
None Explosion safety category for gas None Safety performance level (EN ISO 13849-1) None SIL (IEC 61508) None
Ambient operating temperature - max 70 °C Ambient operating temperature - min -40 °C Diameter sensor 30 mm Number
of contact energized outputs with signalling function 0 Number of contacts (normally open contacts) 1 Number of outputs
(protected contact energized) 0 Number of outputs (protected semiconductor) 0 Number of outputs (semiconductor with
signaling function) 1 Operational current (Ib) in the switched state at 24 V DC 15 A Output current at protected output - max
0 mA Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Functions Protection against wire breakage
Short-circuit protection
Protection against polarity reversal Voltage type DC Mo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / E59-M30C129C02-D1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.