

INDUSTRIAL COMPONENT DATA

UTI1,0-115 206929 Y7-206929 EATON ELECTRIC Its own control transformer, 1p, 1000VA, prim.208-600V/ seco.2x115V

Brand: EATON - MOELLER | Manufacturer Part Number: UTI1,0-115



Manufacturer	EATON - MOELLER
MPN / Reference	UTI1,0-115
Catalog number	Y7-206929
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-A4120D4586
Generated	2026-08-06

Product Overview

Its own control transformer, 1p, 1000VA, prim.208-600V/ seco.2x115V

UTI1,0-115

Eaton Moeller® series UTI Control transformer, 1 kVA, Rated input voltage 208 - 600 V, Rated output voltage 2 x 115 V Control transformer, Product range: Single-phase UTI multi-winding transformers, Rated input voltage: 208 - 600 V, Rated output voltage: 2 x 115 V, Rated power: 1 kVA, Degree of Protection: IP00, Standards Built and tested to: (universal) control, isolating and safety transformers to, VDE 0550, IEC/EN 61558-2-2/2-4/2-6, VDE 0570 Part 2-2/2-6 (safety transformer), VDE 0570 Part 2-4 (isolating transformer), Suitable for use to: IEC/EN 60204-1, ÖVE-EN 13, VDE 0113, VDE 0100 Part 410

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Transformers
--------------	--------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series UTI Control transformer Catalog Number 206929 Model Code UTI1,0-115 EAN 4015082069292 Product Length/Depth 150 mm Product Height 150 mm Product Width 151 mm Product Weight 13.4 kg

Certifications UL Recognized

CSA-C22.2 No. 66.1-06

CSA-C22.2 No. 66.2-06

VDE 0570 Part 2-2/2-6 (safety transformer)

UL report applies to both US and Canada

UL 506

IEC/EN 61558-2-2/2-4/2-6

VDE 0113, VDE 0100 Part 410

IEC/EN 61558-2-2

UL 5085-2

VDE 0550

UL5085-1

CSA-C22.2 No. 66

Certified by UL for use in Canada

VDE 0570 Part 2-4 (isolating transformer)

IEC/EN 60204-1, ÖVE-EN 13

UL File No.: E167225

CE

UL Category Control No.: XPTQ2, XPTQ8 Catalog Notes Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C Features & Functions

Features Reinforced insulation

Fully Vacuum-impregnated

Separate windings General

Ambient operating temperature - min -25 °C Ambient operating temperature - max 40 °C Connection type Terminations

Duty factor 100 % Insulation class B Primary tapping ± 20 % Product category Single-phase UTI multi-winding transformers

Suitable for Branch circuits, (UL/CSA) Electrical rating

Efficiency 92.9 % No-load losses 46 W Rated frequency - min 50 Hz Rated frequency - max 60 Hz Rated power 1 VA

Relative short-circuit voltage 2.1 % Short-circuit losses 30 W Voltage rating - max 600 V Design verification

Equipment heat dis...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / UTI1,0-115 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.