

INDUSTRIAL COMPONENT DATA

UTI0,1-115 206923 Y7-206923 EATON ELECTRIC Its own control transformer, 1p, 100VA, prim.208-600V/ seco.2x115V

Brand: EATON - MOELLER | Manufacturer Part Number: UTI0,1-115



Manufacturer	EATON - MOELLER
MPN / Reference	UTI0,1-115
Catalog number	Y7-206923
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-7BDE562BA3
Generated	2026-08-05

Product Overview

Its own control transformer, 1p, 100VA, prim.208-600V/ seco.2x115V

UTI0,1-115

Eaton Moeller® series UTI Control transformer, 0.1 kVA, Rated input voltage 208 - 600 V, Rated output voltage 2 x 115 V Control transformer, Product range: Single-phase UTI multi-winding transformers, Rated input voltage: 208 - 600 V, Rated output voltage: 2 x 115 V, Rated power: 0.1 kVA, Degree of Protection: IP00, Standards Built and tested to: (universal) control, isolating and safety transformers to, VDE 0550, IEC/EN 61558-2-2/2-4/2-6, VDE 0570 Part 2-2/2-6 (safety transformer), VDE 0570 Part 2-4 (isolating transformer), Suitable for use to: IEC/EN 60204-1, ÖVE-EN 13, VDE 0113, VDE 0100 Part 410

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Transformers**

Additional Product Information

General specifications

Product Name Eaton Moeller® series UTI Control transformer Catalog Number 206923 Model Code UTI0,1-115 EAN

4015082069230 Product Length/Depth 89 mm Product Height 93 mm Product Width 85 mm Product Weight 2 kg

Certifications VDE 0570 Part 2-2/2-6 (safety transformer)

IEC/EN 61558-2-2

UL 5085-2

VDE 0113, VDE 0100 Part 410

CSA-C22.2 No. 66.2-06

UL Recognized

UL 506

UL File No.: E167225

UL report applies to both US and Canada

Certified by UL for use in Canada

VDE 0570 Part 2-4 (isolating transformer)

CSA-C22.2 No. 66

UL Category Control No.: XPTQ2, XPTQ8

IEC/EN 61558-2-2/2-4/2-6

UL5085-1

CE

IEC/EN 60204-1, ÖVE-EN 13

VDE 0550

CSA-C22.2 No. 66.1-06 Catalog Notes Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C Product specifications

Features Reinforced insulation

Fully Vacuum-impregnated

Separate windings 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / UTI0,1-115 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.