

INDUSTRIAL COMPONENT DATA

UTIO,2-115 206924 Y7-206924 EATON ELECTRIC Its own control transformer, 1p, 200VA, prim.208-600V/ seco.2x115V

Brand: EATON - MOELLER | Manufacturer Part Number: UTIO,2-115



Manufacturer	EATON - MOELLER
MPN / Reference	UTIO,2-115
Catalog number	Y7-206924
Category	One-phase control transformer
Minimum order	1 Pcs
Document ID	EO-B7FFE00AC3
Generated	2026-08-05

Product Overview

Its own control transformer, 1p, 200VA, prim.208-600V/ seco.2x115V

UTIO,2-115

Eaton Moeller® series UTI Control transformer, 0.2 kVA, Rated input voltage 208 - 600 V, Rated output voltage 2 x 115 V Control transformer, Product range: Single-phase UTI multi-winding transformers, Rated input voltage: 208 - 600 V, Rated output voltage: 2 x 115 V, Rated power: 0.2 kVA, Degree of Protection: IP00, Standards Built and tested to: (universal) control, isolating and safety transformers to, VDE 0550, IEC/EN 61558-2-2/2-4/2-6, VDE 0570 Part 2-2/2-6 (safety transformer), VDE 0570 Part 2-4 (isolating transformer), Suitable for use to: IEC/EN 60204-1, ÖVE-EN 13, VDE 0113, VDE 0100 Part 410

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Transformers
--------------	--------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series UTI Control transformer Catalog Number 206924 Model Code UTIO,2-115 EAN 4015082069247 Product Length/Depth 82 mm Product Height 112 mm Product Width 106 mm Product Weight 3 kg

Certifications VDE 0113, VDE 0100 Part 410

VDE 0570 Part 2-2/2-6 (safety transformer)

UL 5085-2

IEC/EN 61558-2-2

VDE 0550

UL5085-1

UL Recognized

IEC/EN 61558-2-2/2-4/2-6

VDE 0570 Part 2-4 (isolating transformer)

IEC/EN 60204-1, ÖVE-EN 13

UL 506

UL Category Control No.: XPTQ2, XPTQ8

UL report applies to both US and Canada

CSA-C22.2 No. 66

UL File No.: E167225

CE

Certified by UL for use in Canada

CSA-C22.2 No. 66.1-06

CSA-C22.2 No. 66.2-06 Catalog Notes Electrical characteristics: all details for no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values relate to a temperature of 20 °C Product specifications

Features Reinforced insulation

Separate windings

Fully Vacuum-impregnated 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / UTI0,2-115 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.