


INDUSTRIAL COMPONENT DATA

+IZMX-AS88-1 184170 Y7-184170 EATON ELECTRIC Auxiliary contacts, 8 switched. Can only be sold assembled.

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-AS88-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-AS88-1
Catalog number	Y7-184170
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-2A481B69CA
Generated	2026-08-05

Product Overview

Auxiliary contacts, 8 switched. Can only be sold assembled.

+IZMX-AS88-1

Signalling switch ON-OFF, 8W

Accessories, Standard auxiliary switch for On-Off signaling, The basic device already contains two changeover contacts., 8 additionally integrated changeover contacts are included., For use with IZMX40..., INX40..., 8 changeover contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers IZM**

Additional Product Information

Signalling switch ON-OFF, 8WAccessories, Standard auxiliary switch for On-Off signaling, The basic device already contains two changeover contacts., 8 additionally integrated changeover contacts are included., For use with IZMX40..., INX40..., 8 changeover contacts

General specificationsProduct nameEaton Moeller series IZMX/INX auxiliary contact blockPart no.+IZMX-AS88-1EAN4015081796779Product Length/Depth100 millimetreProduct height100 millimetreProduct width100 millimetreProduct weight0.272 kilogramCompliancesRoHS conformProduct TradenameIZMX/INXProduct TypeAccessoriesProduct Sub TypeAuxiliary contact blockDelivery programTypeAccessoryModelIntegrableSpecial features8 changeover contacts

The basic device already contains two changeover contacts.

8 additionally integrated changeover contacts are included.Used withIZMX40...

INX40...Technical Data - ElectricalRated operational current (Ie) at AC-15, 220 V, 230 V, 240 V10 ARated breaking capacity

(inductive load)0.5 A (125 V DC)

10 A (250 V AC)

0.25 A (250 V DC)Electric connection typeFlat plug-in connectionTechnical Data - MechanicalMounting

MethodOtherNumber of contacts (change-over contacts)8Number of contacts (normally closed contacts)0Number of

contacts (normally open contacts)0Design verification as per IEC/EN 61439 - technical dataAmbient operating temperature

- min-25 °CAmbient operating temperature - max70 °CAdditional informationAccessory/spare part typeAuxiliary contact

ETIM for 184170 Low-voltage industrial controls...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-AS88-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.