

## INDUSTRIAL COMPONENT DATA

# IZMX-CAS403-2500-SEC-1 183947 Y7-183947 EATON ELECTRIC Disp. removable (Chassis) 2500A, IZM403. Terminal blo..

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-CAS403-2500-SEC-1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | IZMX-CAS403-2500-SEC-1             |
| Catalog number  | Y7-183947                          |
| Category        | Chassis part power circuit breaker |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-CF6B353390                      |
| Generated       | 2026-08-06                         |

## Product Overview

Disp. removable (Chassis) 2500A, IZM403. Terminal block complete

IZMX-CAS403-2500-SEC-1

Eaton Moeller series IZMX/INX - ACB. Cassette 2500A, IZMX403 m. control cable connection

Accessories, Cassettes, Equipment supplied: arcing chamber cover, terminal blocks fully populated, Installation type Withdrawable, Rated current In 2500 A, Pole 3, For use with IZMX40...3-...W, INX40...3-...W, Control circuit terminal

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

## Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX cassette Catalog Number 183947 Model Code IZMX-CAS403-2500-SEC-1  
EAN 4015081782734 Product Length/Depth 584 mm Product Height 597 mm Product Width 521 mm Product Weight 29 kg

Compliances RoHS conform Delivery program

Type Accessory Accessory/spare part type Withdrawable units Number of poles Three-pole Amperage Rating 2500 A

Nominal current 2500 A Technical data - electrical

Electrical connection type of main circuit Rail connection Technical data - mechanical

Mounting Method Withdrawable Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Additional information

Features Version as built-in device Special features Used with INX40...3-...W

Three-pole

IZMX40...3-...W

ETIM for 183947 Low-voltage industrial controls and switchgear (EC002043)

Feature Name

Feature Value

Rated current In (EF008250)

2500 A

Number of poles (EF001391)

3

Version as busbar adapter (EF006965)

No

Version as built-in device (EF006954)

Yes

Type of electrical connection of main circuit (EF006819)

Rail connection

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-CAS403-2500-SEC-1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.