

INDUSTRIAL COMPONENT DATA

IZMX-CT-NGS-1 183937 Y7-183937 EATON ELECTRIC

Core-balance transformer

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-CT-NGS-1



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-CT-NGS-1
Catalog number	Y7-183937
Category	Current transformer
Minimum order	1 Pcs
Document ID	EO-73C32E48BB
Generated	2026-07-27

Product Overview

Core-balance transformer

IZMX-CT-NGS-1

Eaton Moeller series IZMX/INX - ACB. Core-balance transformer

Accessories, The core-balance transformer can be used for the earth-fault protection or earth-fault alarm function a) for total current measurements in IZMX16 units or b) for directly measuring the ground fault current at the grounded neutral point., For use with IZMX-DTV-G, +IZMX-DTV-G, +IZMX-DTV-GZ, +IZMX-DTU-A, IZMX-DTU-A, +IZMX-DTU-AZ, +IZMX-DTU-G, IZMX-DTU-G, +IZMX-DTU-AM, IZMX-DTU-AM, +IZMX-DTU-AMZ, IZMX-DTU-GMZ, IZMX-DTU-GM, +IZMX-DTU-GM, +IZMX-DTU-GZ, IZMX-DTP-G, IZMX-DTP-G, +IZMX-DTP-GZ, +IZMX-DTP-GM, +IZMX-DTP-GMZ, IZMX-DTP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX current transformer Catalog Number 183937 Model Code IZMX-CT-NGS-1
EAN 4015081782666 Product Length/Depth 100 mm Product Height 100 mm Product Width 100 mm Product Weight 2.75
kg Compliances RoHS conform Delivery program

Type Accessory Model Wound primary current converter Accessory/spare part type Core-balance transformer Nominal
current 4000 A Technical data - electrical

Secondary rated current 0 A Secondary rated apparent power 0 VA Accuracy class (ratio) Other Secondary connection
Screw connection Technical data - mechanical

Opening diameter 0 mm Opening height - max 220 mm Opening width - max 0 mm Number of inputs (primary) 1 Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Additional information

Fitted with: Copper rail Special features The core-balance transformer can be used for the earth-fault protection or earth-fault alarm function a) for total current measurements in IZMX16 units or b) for directly measuring the ground fault current at the grounded neutral point. Used with +IZMX-DTU-GM

IZMX-DTU-A

+IZMX-DTU-AMZ

+IZMX-DTU-GZ

+IZMX-DTP-GM

+IZMX-DTU-A

IZMX-DTU-GM

+IZMX-DTU-G

IZMX-DTP-G

IZMX-DTU-GMZ

+IZMX-DTU-AZ

+IZMX-DTP-GZ

+IZMX-DTV-GZ

IZMX-DTU-AM

+IZMX-DTV-G

IZMX-DTU-G

IZMX-DTV-G

+IZMX-DTP-GMZ

+IZMX-DTU-AM

IZMX-DTP

ETIM for 183937 Low-voltage industrial controls and switchgear (EC002048)

Feature Name

Feature....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-CT-NGS-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.