

INDUSTRIAL COMPONENT DATA

IZMX-M16-110AD-1 184252 Y7-184252 EATON ELECTRIC Gear reducer Motor 110-125 VDC/VAC

Brand: EATON - MOELLER | Manufacturer Part Number: IZMX-M16-110AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	IZMX-M16-110AD-1
Catalog number	Y7-184252
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-6546ED8D38
Generated	2026-08-05

Product Overview

Gear reducer Motor 110-125 VDC/VAC

IZMX-M16-110AD-1

Eaton Moeller series IZMX/INX - ACB. Motor operator 110-125 VAC/DC, 16

Accessories, Motor operator, The motor automatically tensions the spring force storage mechanism for remote or local actuation., Retrofitting kit, Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage Us 110 - 127 V AC 50/60 Hz, 110 - 125 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom In 2 AC / 1 DC A, max. Anlaufstrom (35ms) In 6 AC / 5 DC A, max. Leistung AC/DC 280 AC / 150 DC VA/W, max. Anlaufleistung (35ms) AC/DC 3 VA/W, For use with IZMX16..., INX16...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX motor operator Catalog Number 184252 Model Code IZMX-M16-110AD-1
EAN 4015081784110 Product Length/Depth 200 mm Product Height 100 mm Product Width 150 mm Product Weight 0.907 kg
Compliances RoHS conform Delivery program

Type Accessory Frame NF Accessory/spare part type Remote switching Technical data - electrical

Voltage type AC/DC Voltage rating 120 V Control voltage operating range 110 - 125 V DC

110 - 127 V AC (50/60 Hz)

0.85 - 1.1 x Us Rated control supply voltage (Us) at AC, 50 Hz - min 110 V Rated control supply voltage (Us) at AC, 50 Hz -

max 127 V Rated control supply voltage (Us) at AC, 60 Hz - min 110 V Rated control supply voltage (Us) at AC, 60 Hz -
max 127 V Rated control supply voltage (Us) at DC - min 110 V Rated control supply voltage (Us) at DC - max 125 V Rated
operational current 2 A AC 50/60 Hz
1 A DC Starting current rating 6 A AC 50/60 Hz, 5 A DC Power consumption 150 W DC
280 VA AC 50/60 Hz Necessary time for charging spring-operated stored energy mechanism at 1 x Us 3 s AC 50/60 Hz
3 s DC Technical data - mechanical
Number of actuation per minute - max 3 Switch drive type Motor drive Design verification as per IEC/EN 61439 - technical
data
Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Additional information
Special features Used with INX16...
IZMX16...
ETIM for 184252 Low-voltage industrial controls and switchgear (EC001030)
Feature Name
Feature Value....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / IZMX-M16-110AD-1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.