

INDUSTRIAL COMPONENT DATA

**+IZMX-M16-230AD-1 184253 Y7-184253 EATON ELECTRIC
Gear reducer Motor 208-240 VDC/VAC. Can only be sold
assem..**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-M16-230AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-M16-230AD-1
Catalog number	Y7-184253
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-5653CE286E
Generated	2026-08-06

Product Overview

Gear reducer Motor 208-240 VDC/VAC. Can only be sold assembled.

+IZMX-M16-230AD-1

Motor operator 208-240 VAC/DC

Accessories, Motor operator, The motor automatically tensions the spring force storage mechanism for remote or local actuation., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 220 - 240 V AC 50/60 Hz, 220 - 250 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom I_n 1 A, max. Anlaufstrom (35ms) I_n 10 A, max. Leistung AC/DC 280 AC / 150 DC VA/W, max. Anlaufleistung (35ms) AC/DC 4 VA/W, For use with IZMX16..., INX16...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers IZM
--------------	--

Additional Product Information

Motor operator 208-240 VAC/DCAccessories, Motor operator, The motor automatically tensions the spring force storage mechanism for remote or local actuation., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage U_s 220 - 240 V AC 50/60 Hz, 220 - 250 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom I_n 1 A, max. Anlaufstrom (35ms) I_n 10 A, max. Leistung AC/DC 280 AC / 150 DC VA/W, max. Anlaufleistung (35ms) AC/DC 4 VA/W, For use with IZMX16..., INX16...Delivery program
Product rangeAccessoriesAccessoriesRemote switchingAccessoriesMotor operatorThe motor automatically tensions the

spring force storage mechanism for remote or local actuation. Maximum operating frequency [Actuations/minute]3 Please note - the circuit-breaker's switching frequency = 60/h Rated control voltage [Us]208 - 240 V AC 50/60 Hz 220 - 250 V DC V Operating range [x US]0,85 - 1,1 Factor For use with IZMX16... INX16... Information about equipment supplied A signaling switch "Spring-operated stored energy mechanism tensioned" message is included as standard. Technical data
Necessary time required for charging the spring-operated stored energy mechanism at 1 x Us 4 s AC 50/60 Hz
4 s DC Rated operational current [In]1 A AC 50/60 Hz
1 A DC A Starting current 10 A AC 50/60 Hz
10 A DC A Power consumption 280 VA AC 50/60 Hz
280 W DC Design verification as per IEC/EN 61439
Temperatura ambiente mínima de funcionamiento -25 °C Temperatura ambiente...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-M16-230AD-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.