

INDUSTRIAL COMPONENT DATA

**+IZMX-M16-60DC-1 184249 Y7-184249 EATON ELECTRIC
Motor operator 60 VDC. Can only be sold assembled.**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-M16-60DC-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-M16-60DC-1
Catalog number	Y7-184249
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-53E22393D4
Generated	2026-08-04

Product Overview

Motor operator 60 VDC. Can only be sold assembled.

+IZMX-M16-60DC-1

Motor operator 60 VDC

Accessories, Motor operator, The motor automatically tensions the spring force storage mechanism for remote or local actuation., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage Us 60 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom In 3 A, max. Anlaufstrom (35ms) In 15 A, max. Leistung AC/DC 150 VA/W, max. Anlaufleistung (35ms) AC/DC 3 VA/W, For use with IZMX16..., INX16...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

General specifications

Product Name Eaton Moeller series IZMX/INX motor operator Catalog Number 184249 Model Code +IZMX-M16-60DC-1
EAN 4015081796908 Product Length/Depth 200 mm Product Height 100 mm Product Width 150 mm Product Weight 0.907
kg Compliances RoHS conform Delivery program

Type Accessory Accessory/spare part type Remote switching Technical data - electrical

Voltage type DC Control voltage operating range 60 V DC

0.85 - 1.1 x Us Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz -
max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V

Rated control supply voltage (Us) at DC - min 60 V Rated control supply voltage (Us) at DC - max 60 V Rated operational current 3 A DC Starting current rating 15 A DC Power consumption 150 W DC Necessary time for charging spring-operated stored energy mechanism at 1 x Us 3 s DC Technical data - mechanical

Number of actuation per minute - max 3 Switch drive type Motor drive Design verification as per IEC/EN 61439 - technical data

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Additional information

Special features Used with IZMX16...

INX16...

ETIM for 184249 Low-voltage industrial controls and switchgear (EC001030)

Feature Name

Feature Value

Type of switch drive (EF008233)

Motor drive

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated control supply voltage AC 60 Hz (EF00397...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-M16-60DC-1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.