

INDUSTRIAL COMPONENT DATA

**+IZMX-M40-110AD-1 184261 Y7-184261 EATON ELECTRIC
Gear Motor , 110-127V AC, 110-125 VDC. Can only be sold as..**

Brand: EATON - MOELLER | Manufacturer Part Number: +IZMX-M40-110AD-1



Manufacturer	EATON - MOELLER
MPN / Reference	+IZMX-M40-110AD-1
Catalog number	Y7-184261
Category	Motor operator for power circuit-breaker
Minimum order	1 Pcs
Document ID	EO-8BE594AF52
Generated	2026-08-06

Product Overview

Gear Motor , 110-127V AC, 110-125 VDC. Can only be sold assembled.

+IZMX-M40-110AD-1

Motor operator 110-125 VAC/DC

Accessories, Motor operator, The motor automatically tensions the spring force storage mechanism for remote or local actuation., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage Us 110 - 127 V AC 50/60 Hz, 110 - 125 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom In 3 AC / 2 DC A, max. Anlaufstrom (35ms) In 9 AC / 7.5 DC A, max. Leistung AC/DC 425 AC / 275 DC VA/W, max. Anlaufleistung (35ms) AC/DC 3 VA/W, For use with IZMX40..., INX40...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Motor operator 110-125 VAC/DCAccessories, Motor operator, The motor automatically tensions the spring force storage mechanism for remote or local actuation., Maximum operating frequency Actuations/minute 3, Please note - the circuit-breaker's switching frequency = 60/h, Rated control voltage Us 110 - 127 V AC 50/60 Hz, 110 - 125 V DC V, Operating range x US 0,85 - 1,1 Factor, max. Betriebsstrom In 3 AC / 2 DC A, max. Anlaufstrom (35ms) In 9 AC / 7.5 DC A, max. Leistung AC/DC 425 AC / 275 DC VA/W, max. Anlaufleistung (35ms) AC/DC 3 VA/W, For use with IZMX40..., INX40...Delivery program

Product rangeAccessoriesAccessoriesRemote switchingAccessoriesMotor operatorThe motor automatically tensions the spring force storage mechanism for remote or local actuation.Maximum operating frequency [Actuations/minute]3Please

note - the circuit-breaker's switching frequency = 60/hRated control voltage [Us]110 - 127 V AC 50/60 Hz
110 - 125 V DC VOperating range [x US]0,85 - 1,1 FactorFor use withIZMX40...
INX40...Information about equipment suppliedA signaling switch "Spring-operated stored energy mechanism tensioned"
message is included as standard.Technical data
Necessary time required for charging the spring-operated stored energy mechanism at 1 x Us6 s AC 50/60 Hz
6 s DCRated operational current [In]3 A AC 50/60 Hz
2 A DC AStarting current9 A AC 50/60 Hz
7.5 A DC APower consumption425 VA AC 50/60 Hz
275 W DCDesign verification as per IEC/EN 61439
Operating ambient temperature min.-25 °COperating....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZMX-M40-110AD-1 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.